



Figure similar

SIPLUS S7-1200 CPU 1212C AC/DC/relay based on 6ES7212-1BE40-0XB0 with conformal coating, -40...+70 °C, start up -25 °C, signal board: 0, compact CPU, AC/DC/relay, onboard I/O: 8 DI 24 V DC; 6 DQ relay 2 A 2 AI 0-10 V DC, power supply: 85-264 V AC at 47-63 Hz, program/data memory 75 KB


| General information  |   |
|--|---|
| Product type designation   | CPU 1212C AC/DC/relay   |
| Engineering with   |   |
| <ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul> | see entry ID: 109746275   |
| Supply voltage   |   |
| Rated value (AC)   |   |
| <ul style="list-style-type: none"> <li>120 V AC</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>230 V AC</li> </ul>   | Yes   |
| permissible range, lower limit (AC)  | 85 V  |
| permissible range, upper limit (AC)  | 264 V   |
| Line frequency   |   |
| <ul style="list-style-type: none"> <li>permissible range, lower limit</li> </ul>                         | 47 Hz   |
| <ul style="list-style-type: none"> <li>permissible range, upper limit</li> </ul>                         | 63 Hz   |
| Input current  |   |
| Current consumption (rated value)  | 80 mA at 120 V AC; 40 mA at 240 V AC                                  |
| Current consumption, max.  | 240 mA at 120 V AC; 120 mA at 240 V AC                                |
| Inrush current, max.   | 20 A; at 264 V  |
| Output current   |   |
| for backplane bus (5 V DC), max.   | 1 000 mA; Max. 5 V DC for SM and CM                                   |
| Encoder supply   |   |
| 24 V encoder supply  |   |
| <ul style="list-style-type: none"> <li>24 V</li> </ul>   | 20.4 to 28.8V   |
| Power loss   |   |
| Power loss, typ.   | 11 W  |
| Memory   |   |
| Work memory  |   |
| <ul style="list-style-type: none"> <li>integrated</li> </ul>   | 75 kbyte  |
| Load memory  |   |
| <ul style="list-style-type: none"> <li>integrated</li> </ul>   | 1 Mbyte   |
| <ul style="list-style-type: none"> <li>Plug-in (SIMATIC Memory Card), max.</li> </ul>                    | with SIMATIC memory card  |
| Backup   |   |
| <ul style="list-style-type: none"> <li>present</li> </ul>  | Yes; maintenance-free   |
| <ul style="list-style-type: none"> <li>without battery</li> </ul>  | Yes   |
| CPU processing times   |   |
| for bit operations, typ.   | 0.085 µs; / Operation   |
| for word operations, typ.  | 1.7 µs; / Operation   |
| for floating point arithmetic, typ.  | 2.3 µs; / Operation   |
| CPU-blocks   |   |
| Number of blocks (total)   | DBs, FCs, FBs, counters and timers. The maximum number of addressable |

|  |   |
|--|---|
|  | blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used |
| <b>OB</b>  |   |
| <ul style="list-style-type: none"> <li>• Number, max.</li> </ul>   | Limited only by RAM for code  |
| <b>Data areas and their retentivity</b>  |   |
| Retentive data area (incl. timers, counters, flags), max.  | 10 kbyte  |
| <b>Flag</b>  |   |
| <ul style="list-style-type: none"> <li>• Size, max.</li> </ul>   | 4 kbyte; Size of bit memory address area  |
| <b>Local data</b>  |   |
| <ul style="list-style-type: none"> <li>• per priority class, max.</li> </ul>   | 16 kbyte; Priority class 1 (program cycle): 16 KB, priority class 2 to 26: 6 KB               |
| <b>Address area</b>  |   |
| <b>Process image</b>   |   |
| <ul style="list-style-type: none"> <li>• Inputs, adjustable</li> <li>• Outputs, adjustable</li> </ul>                                    | 1 kbyte<br>1 kbyte  |
| <b>Hardware configuration</b>  |   |
| Number of modules per system, max.   | 3 com. modules, no signal board can be used, 2 signal modules                                 |
| <b>Time of day</b>   |   |
| <b>Clock</b>   |   |
| <ul style="list-style-type: none"> <li>• Hardware clock (real-time)</li> <li>• Backup time</li> <li>• Deviation per day, max.</li> </ul> | Yes<br>480 h; Typical<br>60 s/month at 25 °C  |
| <b>Digital inputs</b>  |   |
| Number of digital inputs   | 8; Integrated   |
| <ul style="list-style-type: none"> <li>• of which inputs usable for technological functions</li> </ul>                                   | 4; HSC (High Speed Counting)  |
| Source/sink input  | Yes   |
| <b>Number of simultaneously controllable inputs</b>  |   |
| all mounting positions   |   |
| — up to 40 °C, max.  | 8   |
| <b>Input voltage</b>   |   |
| <ul style="list-style-type: none"> <li>• Rated value (DC)</li> <li>• for signal "0"</li> <li>• for signal "1"</li> </ul>                 | 24 V<br>5 V DC at 1 mA<br>15 V DC at 2.5 mA   |
| <b>Input current</b>   |   |
| <ul style="list-style-type: none"> <li>• for signal "1", typ.</li> </ul>   | 1 mA  |
| <b>Input delay (for rated value of input voltage)</b>  |   |
| for standard inputs  |   |
| — parameterizable  | 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four      |
| — at "0" to "1", min.  | 0.2 ms  |
| — at "0" to "1", max.  | 12.8 ms   |
| for interrupt inputs   |   |
| — parameterizable  | Yes   |
| for technological functions  |   |
| — parameterizable  | Yes; Single phase : 3 at 100 kHz & 3 at 30 kHz, differential: 3 at 80 kHz & 3 at 30 kHz       |
| <b>Cable length</b>  |   |
| <ul style="list-style-type: none"> <li>• shielded, max.</li> <li>• unshielded, max.</li> </ul>   | 500 m; 50 m for technological functions<br>300 m; for technological functions: No             |
| <b>Digital outputs</b>   |   |
| Number of digital outputs  | 6; Relays   |
| <b>Switching capacity of the outputs</b>   |   |
| <ul style="list-style-type: none"> <li>• with resistive load, max.</li> <li>• on lamp load, max.</li> </ul>                              | 2 A<br>30 W with DC, 200 W with AC  |
| <b>Output delay with resistive load</b>  |   |
| <ul style="list-style-type: none"> <li>• "0" to "1", max.</li> <li>• "1" to "0", max.</li> </ul>   | 10 ms; max.<br>10 ms; max.  |
| <b>Switching frequency</b>   |   |
| <ul style="list-style-type: none"> <li>• of the pulse outputs, with resistive load, max.</li> </ul>                                      | 1 Hz  |
| <b>Relay outputs</b>   |   |
| <ul style="list-style-type: none"> <li>• Number of relay outputs</li> <li>• Number of operating cycles, max.</li> </ul>                  | 6<br>mechanically 10 million, at rated load voltage 100 000                                   |

|   |                             |
|---|-----------------------------|
| <b>Cable length</b>   |                             |
| • shielded, max.  | 500 m                       |
| • unshielded, max.  | 150 m                       |
| <b>Analog inputs</b>  |                             |
| Number of analog inputs                                       | 2                           |
| <b>Input ranges</b>   |                             |
| • Voltage   | Yes                         |
| <b>Input ranges (rated values), voltages</b>                  |                             |
| • 0 to +10 V  | Yes                         |
| — Input resistance (0 to 10 V)                                | ≥100k ohms                  |
| <b>Cable length</b>   |                             |
| • shielded, max.  | 100 m; twisted and shielded |
| <b>Analog outputs</b>   |                             |
| Number of analog outputs                                      | 0                           |
| <b>Analog value generation for the inputs</b>                 |                             |
| <b>Integration and conversion time/resolution per channel</b> |                             |
| • Resolution with overrange (bit including sign), max.        | 10 bit                      |
| • Integration time, parameterizable                           | Yes                         |
| • Conversion time (per channel)                               | 625 μs                      |
| <b>Encoder</b>  |                             |
| <b>Connectable encoders</b>                                   |                             |
| • 2-wire sensor   | Yes                         |
| <b>1. Interface</b>   |                             |
| Interface type  | PROFINET                    |
| Isolated  | Yes                         |
| automatic detection of transmission rate                      | Yes                         |
| Autonegotiation   | Yes                         |
| Autocrossing  | Yes                         |
| <b>Interface types</b>  |                             |
| • RJ 45 (Ethernet)  | Yes                         |
| <b>Protocols</b>  |                             |
| • PROFINET IO Controller                                      | Yes                         |
| • PROFINET IO Device  | Yes                         |
| • Open IE communication                                       | Yes                         |
| • Web server  | Yes                         |
| <b>PROFINET IO Controller</b>                                 |                             |
| • Transmission rate, max.                                     | 100 Mbit/s                  |
| <b>Services</b>   |                             |
| — Number of connectable IO Devices, max.                      | 16                          |
| <b>PROFINET IO Device</b>                                     |                             |
| <b>Services</b>   |                             |
| — Shared device   | Yes                         |
| — Number of IO Controllers with shared device, max.           | 2                           |
| <b>Protocols</b>  |                             |
| Supports protocol for PROFINET IO                             | Yes                         |
| PROFIsafe   | No                          |
| PROFIBUS  | Yes; CM 1243-5 required     |
| AS-Interface  | Yes                         |
| <b>Protocols (Ethernet)</b>                                   |                             |
| • TCP/IP  | Yes                         |
| <b>Open IE communication</b>                                  |                             |
| • TCP/IP  | Yes                         |
| • ISO-on-TCP (RFC1006)  | Yes                         |
| • UDP   | Yes                         |
| <b>Web server</b>   |                             |
| • supported   | Yes                         |
| • User-defined websites                                       | Yes                         |
| <b>Further protocols</b>                                      |                             |
| • MODBUS  | Yes                         |
| <b>communication functions / header</b>                       |                             |

|  |   |
|--|---|
| <b>S7 communication</b>  |   |
| • supported  | Yes   |
| • as server  | Yes   |
| • as client  | Yes   |
| <b>Number of connections</b>   |   |
| • overall  | 16; dynamically   |
| <b>Test commissioning functions</b>  |   |
| <b>Status/control</b>  |   |
| • Status/control variable  | Yes   |
| • Variables  | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters  |
| <b>Forcing</b>   |   |
| • Forcing  | Yes   |
| <b>Diagnostic buffer</b>   |   |
| • present  | Yes   |
| <b>Traces</b>  |   |
| • Number of configurable Traces  | 2; Up to 512 KB of data per trace are possible  |
| <b>Integrated Functions</b>  |   |
| Frequency measurement  | Yes   |
| controlled positioning   | Yes   |
| Number of position-controlled positioning axes, max.   | 8   |
| PID controller   | Yes   |
| Number of alarm inputs   | 4   |
| <b>Potential separation</b>  |   |
| <b>Potential separation digital inputs</b>   |   |
| • Potential separation digital inputs  | 500V AC for 1 minute  |
| • between the channels, in groups of   | 1   |
| <b>Potential separation digital outputs</b>  |   |
| • Potential separation digital outputs   | Relays  |
| • between the channels   | No  |
| • between the channels, in groups of   | 2   |
| <b>EMC</b>   |   |
| <b>Interference immunity against discharge of static electricity</b>                                 |   |
| • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2                | Yes   |
| — Test voltage at air discharge  | 8 kV  |
| — Test voltage at contact discharge  | 6 kV  |
| <b>Interference immunity to cable-borne interference</b>   |   |
| • Interference immunity on supply lines acc. to IEC 61000-4-4  | Yes   |
| • Interference immunity on signal cables acc. to IEC 61000-4-4                                       | Yes   |
| <b>Interference immunity against voltage surge</b>   |   |
| • Interference immunity on supply lines acc. to IEC 61000-4-5  | Yes   |
| <b>Interference immunity against conducted variable disturbance induced by high-frequency fields</b> |   |
| • Interference immunity against high-frequency radiation acc. to IEC 61000-4-6                       | Yes   |
| <b>Emission of radio interference acc. to EN 55 011</b>  |   |
| • Limit class A, for use in industrial areas   | Yes; Group 1  |
| • Limit class B, for use in residential areas  | Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011  |
| <b>Degree and class of protection</b>  |   |
| IP degree of protection  | IP20  |
| <b>Ambient conditions</b>  |   |
| <b>Free fall</b>   |   |
| • Fall height, max.  | 0.3 m; five times, in product package   |
| <b>Ambient temperature during operation</b>  |   |
| • min.   | -40 °C; = Tmin; Startup @ -25 °C  |
| • max.   | 70 °C; = Tmax; Tmax > +55 °C number of simultaneously switched-on digital inputs 4, digital outputs 3, analog inputs 2 (no adjacent points) with horizontal mounting position; Tmax > +60 °C number of simultaneously switched-on digital inputs 3, digital outputs 2, analog inputs 0 (no adjacent points) with horizontal mounting position |

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>vertical installation, min.</li> <li>vertical installation, max.</li> <li>At cold restart, min.</li> </ul>   | <p>-40 °C; = Tmin; Startup @ -25 °C</p> <p>50 °C; = Tmax</p> <p>-25 °C</p>  |
| <b>Ambient temperature during storage/transportation</b>  |   |
| <ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>  | <p>-40 °C</p> <p>70 °C</p>  |
| <b>Altitude during operation relating to sea level</b>  |   |
| <ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> <li>Ambient air temperature-barometric pressure-altitude</li> </ul>   | <p>2 000 m</p> <p>Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m); above 2 000 m max. 132 V AC</p> |
| <b>Relative humidity</b>  |   |
| <ul style="list-style-type: none"> <li>With condensation, tested in accordance with IEC 60068-2-38, max.</li> </ul>   | 100 %; RH incl. condensation/frost (no commissioning under condensation conditions)   |
| <b>Vibrations</b>   |   |
| <ul style="list-style-type: none"> <li>Vibration resistance during operation acc. to IEC 60068-2-6</li> <li>Operation, tested according to IEC 60068-2-6</li> </ul>   | <p>2 g (m/s<sup>2</sup>) wall mounting, 1 g (m/s<sup>2</sup>) DIN rail</p> <p>Yes</p>   |
| <b>Shock testing</b>  |   |
| <ul style="list-style-type: none"> <li>tested according to IEC 60068-2-27</li> </ul>  | Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms   |
| <b>Resistance</b>   |   |
| <b>Coolants and lubricants</b>  |   |
| <ul style="list-style-type: none"> <li>Resistant to commercially available coolants and lubricants</li> </ul>   | Yes; Incl. diesel and oil droplets in the air   |
| <b>Use in stationary industrial systems</b>   |   |
| <ul style="list-style-type: none"> <li>to biologically active substances according to EN 60721-3-3</li> <li>to chemically active substances according to EN 60721-3-3</li> <li>to mechanically active substances according to EN 60721-3-3</li> </ul>   | <p>Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request</p> <p>Yes; Class 3C4 (RH &lt; 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *</p> <p>Yes; Class 3S4 incl. sand, dust, *</p>              |
| <b>Use on ships/at sea</b>  |   |
| <ul style="list-style-type: none"> <li>to biologically active substances according to EN 60721-3-6</li> <li>to chemically active substances according to EN 60721-3-6</li> <li>to mechanically active substances according to EN 60721-3-6</li> </ul>   | <p>Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request</p> <p>Yes; Class 6C3 (RH &lt; 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *</p> <p>Yes; Class 6S3 incl. sand, dust; *</p>                                   |
| <b>Usage in industrial process technology</b>   |   |
| <ul style="list-style-type: none"> <li>Against chemically active substances acc. to EN 60654-4</li> <li>Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04</li> </ul>   | <p>Yes; Class 3 (excluding trichlorethylene)</p> <p>Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)</p>                         |
| <b>Remark</b>   |   |
| <ul style="list-style-type: none"> <li>Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04</li> </ul>   | * The supplied plug covers must remain in place over the unused interfaces during operation!  |
| <b>Conformal coating</b>  |   |
| <ul style="list-style-type: none"> <li>Coatings for printed circuit board assemblies acc. to EN 61086</li> <li>Protection against fouling acc. to EN 60664-3</li> <li>Military testing according to MIL-I-46058C, Amendment 7</li> <li>Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A</li> </ul> | <p>Yes; Class 2 for high reliability</p> <p>Yes; Type 1 protection</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p>   |
| <b>configuration / header</b>   |   |
| <b>configuration / programming / header</b>   |   |
| <b>Programming language</b>   |   |
| <ul style="list-style-type: none"> <li>LAD</li> <li>FBD</li> <li>SCL</li> </ul>   | <p>Yes</p> <p>Yes</p> <p>Yes</p>  |
| <b>programming / cycle time monitoring / header</b>   |   |
| <ul style="list-style-type: none"> <li>adjustable</li> </ul>  | Yes   |
| <b>Dimensions</b>   |   |
| Width   | 90 mm   |

|                       |   |
|-----------------------|---|
| Height                | 100 mm  |
| Depth                 | 75 mm   |
| <b>Weights</b>        |   |
| Weight, approx.       | 425 g   |
| <b>last modified:</b> | 9/12/2023  |