

# SIEMENS

## Product data sheet

6AG1231-4HD30-2XB0



SIPLUS S7-1200 SM231 AI 4 12BIT -25 ... +70  
DEGREES C WITH CONFORMAL COATING BASED  
ON 6ES7231-4HD30-0XB0 . ANALOG INPUT,  
4 AI, +/-10V, +/-5V, +/-2.5V,  
OR 0-20 MA 12 BIT + SIGN BIT (13 BIT ADC)

Supply voltage	
24 V DC	Yes
Input current	
Current consumption, typ.	45 mA
from backplane bus 5 V DC, typ.	80 mA
Power losses	
Power loss, typ.	1.5 W
Analog inputs	
Number of analog inputs	4 ; Current or voltage differential inputs
permissible input frequency for current input (destruction limit), max.	± 35 V
permissible input voltage for voltage input (destruction limit), max.	35 V
permissible input current for voltage input (destruction limit), max.	40 mA
Cycle time (all channels) max.	625 µs

permissible input current for current input (destruction limit), max.	40 mA
<b>Input ranges</b>	
Voltage	Yes ; $\pm 10$ V, $\pm 5$ V, $\pm 2.5$ V
Current	Yes ; 0 to 20 mA
Thermocouple	No
Resistance thermometer	No
Resistance	No
<b>Input ranges (rated values), voltages</b>	
-10 V to +10 V	Yes
Input resistance (-10 V to +10 V)	$\geq 9$ MOhm
-2.5 V to +2.5 V	Yes
Input resistance (-2.5 V to +2.5 V)	$\geq 9$ MOhm
-5 V to +5 V	Yes
Input resistance (-5 V to +5 V)	$\geq 9$ MOhm
<b>Input ranges (rated values), currents</b>	
0 to 20 mA	Yes
Input resistance (0 to 20 mA)	280 $\Omega$
<b>Thermocouple (TC)</b>	
Temperature compensation	
Parameterizable	No
<b>Analog outputs</b>	
Number of analog outputs	0
<b>Analog value creation</b>	
<b>Integrations and conversion time/ resolution per channel</b>	
Resolution with overrange (bit including sign), max.	12 bit ; + sign
Integration time, parameterizable	Yes
Interference voltage suppression for interference frequency f1 in Hz	40 dB, DC to 60 V for interference frequency 50 / 60 Hz
<b>Smoothing of measured values</b>	
Parameterizable	Yes
Step: None	Yes
Step: low	Yes

Step: Medium	Yes
Step: High	Yes
<b>Errors/accuracies</b>	
Temperature error (relative to input area)	25 °C ±0.1 % to 55 °C ±0.2 % total measurement range
<b>Basic error limit (operational limit at 25 °C)</b>	
Voltage, relative to input area	+/- 0,1 %
Current, relative to input area	+/- 0,1 %
<b>Interference voltage suppression for <math>f = n \times (f_l \pm 1\%)</math>, <math>f_l</math> = interference frequency</b>	
common mode voltage, max.	12 V
<b>Interrupts/diagnostics/status information</b>	
<b>Alarms</b>	
Alarms	Yes
Diagnostic alarm	Yes
<b>Diagnostic messages</b>	
Diagnostic functions	Yes
Monitoring the supply voltage	Yes
Wire break	No
<b>Diagnostics indication LED</b>	
for status of the inputs	Yes
for maintenance	Yes
<b>Galvanic isolation</b>	
<b>Galvanic isolation analog outputs</b>	
between the channels and the power supply of the electronics	No
<b>Degree and class of protection</b>	
IP20	Yes
<b>Standards, approvals, certificates</b>	
CE mark	Yes
FM approval	Yes
<b>Ambient conditions</b>	
Extended ambient conditions	

Relative to ambient temperature-atmospheric pressure-installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity	
with condensation / maximum	100 % ; Relative humidity, incl. condensation / frost permitted (no commissioning under condensation conditions)
Resistance	
to biologically active substances / conformity with EN 60721-3-3	Yes
to chemically active substances / conformity with EN 60721-3-3	Yes ; Class 3C4 incl. salt spray according to EN 60068-2-52 (degree of severity 3). The supplied connector covers must remain on the unused interfaces during operation!
to mechanically active substances / conformity with EN 60721-3-3	Yes ; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!
Climatic and mechanical conditions for storage and transport	
Climatic conditions for storage and transport	
Free fall	
Drop height, max. (in packaging)	0.3 m ; five times, in dispatch package
Temperature	
Permissible temperature range	-40 °C to +70 °C
Mechanical and climatic conditions during operation	
Climatic conditions in operation	
Temperature	
Min.	-25 °C ; = Tmin
max.	70 °C ; = Tmax
Connection method	
required front connector	Yes
Mechanics/material	
Type of housing (front)	
Plastic	Yes
Dimensions	
Width	45 mm

Height	100 mm
Depth	75 mm
Weight	
Weight, approx.	180 g
Status	Jul 17, 2012