

Specifications :

LCD Size	19"
Input Interface	Analog VGA + DVI-D
Max Resolution	1280 x 1024
Brightness (cd/m ²)	300
Contrast Ratio	800 : 1
Display Color	16.7M
Pixel Pitch (mm)	0.294
Front Frame	Stainless Steel
Chassis	Heavy-duty Steel
View Angle (H/V)	160/160
OSD function	Yes
Smart OSD	Yes
Mounting	Panel/Wall/Arm(100x100)/Stand
Color	Silver
Dimension(W x H x D mm)	482.6 x 399 x 71.6
Operating Temperature	0 ~ 50°C
Front Panel Protection	IP65 Compliant
Net Weight	10.75kg
Power Adapter	45W, 63000-UP451E12P81L-RS

Ordering Information :

Part No.	Description
SDM-190G-R11/T-R	19" 300cd/m ² SXGA LCD Monitor with VGA and DVI-D input, Stainless Steel Front Panel, Silver Color, W/19" Touch Screen, RoHS
ISDM-190GM-R11/T-R	19" 300cd/m ² SXGA LCD Monitor with VGA and DVI-D input and 9~36V DC Input, Stainless Steel Front Panel, W/19" Touch Screen, RoHS
ISDM-190G-USB-R11/T-R	19" 300cd/m ² SXGA LCD Monitor with VGA and DVI-D input, Stainless Steel Front Panel, W/19" USB Touch Screen, RoHS
ISDM-190GM-USB-R11/T-R	19" 300cd/m ² SXGA LCD Monitor with VGA and DVI-D input and 9~36V DC Input, Stainless Steel Front Panel, W/19" USB Touch Screen, RoHS

Packing List :

1 * AC Power Cable	1 * VGA Cable
1 * 45W AC Power Adapter	1 * User Manual
1 * Power Cable for Terminal Block (For M model ONLY)	1 * Touch Screen RS-232 Cable / Touch Pen / Driver CDROM (For T-R model ONLY)
1 * Touch Screen USB Cable / Touch Pen / Driver CDROM 1 x Touch Screen USB Cable / Touch Pen / Driver CDROM	