

product type designation



Figure similar

SIPLUS NET CP 342-5

SIPLUS NET CP 342-5 PROFIBUS based on 6GK7342-5DA03-0XE0 with conformal coating, -25...+70 °C, communications processor CP 342-5 for connecting SIMATIC S7-300 to PROFIBUS, DP, S5-compatible, PG/OP and S7 communication

transfer rate

transfer rate	
• at the 1st interface / according to PROFIBUS	9.6 kbit/s ... 12 Mbit/s

interfaces

number of interfaces / according to Industrial Ethernet	0
number of electrical connections	
• at the 1st interface / according to PROFIBUS	1
• for power supply	1
type of electrical connection	
• at the 1st interface / according to PROFIBUS	9-pin Sub-D socket (RS485)
• for power supply	4-pole terminal block

supply voltage, current consumption, power loss

type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
supply voltage / external	24 V
relative positive tolerance / at DC / at 24 V	20 %
relative negative tolerance / at DC / at 24 V	15 %
consumed current	
• from backplane bus / at DC / at 5 V / typical	0.15 A
• from external supply voltage / at DC / at 24 V / typical	0.25 A
power loss [W]	6.75 W

ambient conditions

ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
relative humidity	
• with condensation / according to IEC 60068-2-38 / maximum	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
resistance to biologically active substances	
• conformity according to EN 60721-3-3	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request
• conformity according to EN 60721-3-6	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances	

<ul style="list-style-type: none"> conformity according to EN 60721-3-3 	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation.
<ul style="list-style-type: none"> conformity according to EN 60721-3-6 	Yes
resistance to mechanically active substances	
<ul style="list-style-type: none"> conformity according to EN 60721-3-3 	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
<ul style="list-style-type: none"> conformity according to EN 60721-3-6 	Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of test / of the coating / according to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-300 single width
width	40 mm
height	125 mm
depth	120 mm
net weight	0.3 kg
product features, product functions, product components / general	
number of units	
<ul style="list-style-type: none"> per CPU / maximum 	4
performance data / open communication	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	16
data volume	
<ul style="list-style-type: none"> as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	240 byte
performance data / PROFIBUS DP	
service / as DP master	
<ul style="list-style-type: none"> DPV0 	Yes
number of DP slaves	
<ul style="list-style-type: none"> on DP master / operable 	124
data volume	
<ul style="list-style-type: none"> of the address range of the inputs / as DP master / total 	2160 byte
<ul style="list-style-type: none"> of the address range of the outputs / as DP master / total 	2160 byte
<ul style="list-style-type: none"> of the address range of the inputs / per DP slave 	244 byte
<ul style="list-style-type: none"> of the address range of the outputs / per DP slave 	244 byte
<ul style="list-style-type: none"> of the address range of the diagnostic data / per DP slave 	240 byte
service / as DP slave	
<ul style="list-style-type: none"> DPV0 	Yes
data volume	
<ul style="list-style-type: none"> of the address range of the inputs / as DP slave / total 	240 byte
<ul style="list-style-type: none"> of the address range of the outputs / as DP slave / total 	240 byte
performance data / S7 communication	
number of possible connections / for S7 communication	
<ul style="list-style-type: none"> maximum 	16
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	
<ul style="list-style-type: none"> without DP / maximum 	32
<ul style="list-style-type: none"> with DP / maximum 	28
performance data / telecontrol	
protocol / is supported	
<ul style="list-style-type: none"> TCP/IP 	No
product functions / management, configuration, engineering	
configuration software	
<ul style="list-style-type: none"> required 	STEP 7 V5.1 SP2 or higher / STEP 7 Professional V12 (TIA Portal) or higher
further information / internet links	

internet link	<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAX-Download-Manager • to website: Industry Online Support
	http://www.siemens.com/snst http://www.siemens.com/simatic-net http://www.siemens.com/industrial-controls/mall http://www.siemens.com/automation/net/catalog http://automation.siemens.com/bilddb http://www.siemens.com/cax http://support.automation.siemens.com
security information	
security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)</p>

last modified:

10/9/2023 