

■LCD Modules

<For industrial appliances>

Display size (cm) ["]	Model No.	Dot format H × V (dot)	Pixel pitch H × V (mm)	Active area H × V (mm)	Display colors	Lumi- nance (cd/m²) (TYP.)	Interface	Power con- sumption (W) (TYP.)	Outline dimensions*1 W × H × D (mm) (TYP.)	Weight (g) (MAX.)	Remarks
8.8 [3.5]	LQ035Q3DG03	320 × RGB × 240	0.2205 × 0.2205	70.56 × 52.92	16.19 M	450	CMOS	0.8	76.9 × 63.9 × 4.7	TYP. 42	Long-life LED backlight
8.9 [3.5]	LQ035Q3DY01	240 × RGB × 320	0.2235 × 0.2235	53.64 × 71.52	260 k	600	CMOS	0.5	65.0 × 85.0 × 3.4	40	Advanced Super V, Low reflection technology
9.4 [3.7]	LS037V7DW05	480 × RGB × 640	0.117 × 0.117	56.16 × 74.88	16.77 M	250	CMOS	0.4	65.0 × 89.2 × 4.4	50	Advanced Super V, Transflective LCD, With resistive touch panel
	LS037V7DW06					300			65.0 × 89.2 × 3.6	38	Advanced Super V, Transflective LCD
11 [4.2]	LQ042T1DW01	480 × 272 × RGB	0.1935 × 0.1935	92.88 × 52.632	16.19 M	400	CMOS	2.5	109.5 × 69.0 × 9.6	85	Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
11 [4.3]	LQ043T1DG38G	480 × 272 × RGB	0.198 × 0.198	95.04 × 53.856	16.77 M	300	CMOS	0.6	105.5 × 67.2 × 4.2	61	With resistive touch panel
	☆LQ043T1DG39G					360			105.5 × 67.2 × 3.1	46	
	LQ043Y1DY01	480 × RGB × 800	0.117 × 0.117	56.16 × 93.6		315			62.46 × 105.9 × 2.1	30	Advanced Super V, Low reflection technology
14 [5.7]	LQ057Q3DC03	320 × 240 × RGB	0.36 × 0.36	115.2 × 86.4	260 k	500	CMOS	2.5	144.0 × 104.6 × 12.3	210	Long-life LED backlight, Built- in LED backlight driver circuit
16 [6.4]	LQ064X3LW01	1 024 × RGB × 768	0.12675 × 0.12675	129.792 × 97.344	16.77 M	350	LVDS	5.3	153.4 × 122.0 × 9.9	220	Advanced Super V, Long-life LED backlight, Built- in LED backlight driver circuit
18 [7.0]	LQ070Y3LW01	800 × 480 × RGB	0.1905 × 0.1905	152.4 × 91.44	16.19 M	380	LVDS	2.7	170.0 × 110.0 × 9.0	TYP. 175	Advanced Super V, Long-life LED backlight
21 [8.4]	LQ084V1DG43	640 × RGB × 480	0.267 × 0.267	170.88 × 128.16	260 k	370	CMOS	4.7	221.0 × 152.4 × 9.3	340	Long-life LED backlight, Built- in LED backlight driver circuit
	LQ084S3LG03	800 × RGB × 600	0.213 × 0.213	170.4 × 127.8	16.19 M	330	LVDS	4.1	199.5 × 154.0 × 11.6	320	Long-life LED backlight, Built- in LED backlight driver circuit
23 [9.1]	LQ091B1LW01	822 × RGB × 260	0.267 × 0.267	219.474 × 69.42	16.77 M	380	LVDS	6.8	240.0 × 86.0 × 10.0	230	Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
26 [10.1]	LQ101K1LY05	1 280 × RGB × 800	0.1695 × 0.1695	216.96 × 135.6	16.77 M	400	LVDS	4.2	230.7 × 152.5 × 8.7	270	Advanced Super V, Low reflection technology, Long- life LED backlight, Built-in LED backlight driver circuit
	LQ101W3LG01	1 024 × RGB × 600	0.2175 × 0.2088	222.72 × 125.28	260 k	350		5.1	235.3 × 143.0 × 7.9	350	Long-life LED backlight, Built- in LED backlight driver circuit
26 [10.4]	☆LQ104V1DG74	640 × RGB × 480	0.33 × 0.33	211.2 × 158.4	260 k	370	CMOS	(3.4)	227.3 × 177.5 × 9.3	500	Long-life LED backlight, Built- in LED backlight driver circuit
	LQ104V1DG81/LG81					450	CMOS/ LVDS	5.6	246.5 × 179.3 × 12.5	TYP. 500	Long-life LED backlight, Built- in LED backlight driver circuit
	LQ104S1DG2C	800 × RGB × 600	0.264 × 0.264			350	CMOS	4.5	246.5 × 179.3 × 11.0	550	Long-life LED backlight, Built- in LED backlight driver circuit
	★LQ104S1LG74				16.19M	450	LVDS	5.9	227.3 × 177.5 × 9.3	500	Long-life LED backlight, Built- in LED backlight driver circuit
	LQ104S1LG81				260 k	420	LVDS	6.1	246.5 × 179.3 × 12.5	500	Long-life LED backlight, Built- in LED backlight driver circuit

All products listed on this page are LED backlight models.

*1 Protrusions such as positioning bosses are not included.

Note: Please note that the specifications are subject to change without prior notice for product improvement.

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP.

*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

■LCD Modules

<For industrial appliances> (cont'd)

Display size (cm) ["]	Model No.	Dot format H × V (dot)	Pixel pitch H × V (mm)	Active area H × V (mm)	Display colors	Lumi- nance (cd/m ²) (TYP.)	Interface	Power con- sumption (W) (TYP.)	Outline dimensions*1 W × H × D (mm) (TYP.)	Weight (g) (MAX.)	Remarks
31 [12.1]	LQ121S1DG81	800 × RGB × 600	0.3075 × 0.3075	246.0 × 184.5	260 k	450	CMOS	6.2	276.0 × 209.0 × 11.0	650	Long-life LED backlight, Built- in LED backlight driver circuit
	LQ121S1LG84				260 k	450	LVDS	5.1	276.0 × 209.0 × 9.1	600	Long-life LED backlight, Built- in LED backlight driver circuit
	LQ121S1LG86					1 500		12.9			Long-life LED backlight, Built- in LED backlight driver circuit
	LQ121K1LG52	1 280 × RGB × 800	0.204 × 0.204	261.1 × 163.2	16.19 M	430		6.0	278.0 × 184.0 × 8.6	550	Long-life LED backlight, Built-in LED backlight driver circuit
	LQ121K1LW56				16.77 M	320		5.2	278.0 × 184.0 × 10.2		Wide Viewing Angle Long-life LED backlight, Built- in LED backlight driver circuit
	LQ121K1LG58				16.19 M	700		5.8	278.0 × 184.0 × 8.6		Long-life LED backlight, Built- in LED backlight driver circuit
	LQ121X3LG02	1 024 × RGB × 768	0.240 × 0.240	245.8 × 184.3	260 k	1 200		9.7	259.0 × 205.0 × 7.5		
38 [15.0]	LQ150X1LG11	1 024 × RGB × 768	0.297 × 0.297	304.1 × 228.1	16.19 M	600	LVDS	8.2	331.6 × 254.7 × 9.3	950	Long-life LED backlight, Built- in LED backlight driver circuit
	LQ150X1LG91					350		6.8	326.5 × 253.5 × 9.6		Long-life LED backlight, Built- in LED backlight driver circuit
	LQ150X1LG96					1 050		14.8			Built-in LED backlight driver circuit
	LQ150X1LX92				16.19 M	270		10.0			Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit, Haze value 3%
	LQ150X1LX95					400					Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit, Haze value 3%
	LQ150X1LX96					500					Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit, Haze value 3%
	LQ150X1LX9K				16.19 M	400					Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit, Polarized sunglasses supported
	LQ150X1LW12				10 M	350		10.2	331.6 × 254.7 × 9.3		Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
	LQ150X1LW95				16.19 M	400		10.0	326.5 × 253.5 × 9.6		Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
	LQ150X1LW96					500					Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit

All products listed on this page are LED backlight models.

*1 Protrusions such as positioning bosses are not included.

Note: Please note that the specifications are subject to change without prior notice for product improvement.

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP.

*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

■LCD Modules

<For industrial appliances> (cont'd)

Display size (cm) ["]	Model No.	Dot format H × V (dot)	Pixel pitch H × V (mm)	Active area H × V (mm)	Display colors	Luminance (cd/m ²) (TYP.)	Interface	Power consumption (W) (TYP.)	Outline dimensions*1 W × H × D (mm) (TYP.)	Weight (g) (MAX.)	Remarks
40 [15.6]	LQ156T3LW03	1 366 × RGB × 768	0.252 × 0.252	344.232 × 193.536	16.77 M	400	LVDS	16.9	363.8 × 215.9 × 10.8	950	Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
	LQ156M1LG21	1 920 × RGB × 1 080	0.17925 × 0.17925	344.16 × 193.59	16.19 M	300/350/400/600	2ch LVDS	13.6 (600cd/m ²)	370.0 × 217.0 × 9.3		Long-life LED backlight, Built-in LED backlight driver circuit, With brightness control switch
	LQ156M3LW01				16.77 M	400		17.9	363.8 × 215.9 × 10.8		Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
48 [19.0]	LQ190E1LW52	1 280 × RGB × 1 024	0.294 × 0.294	376.32 × 301.056	16.77 M	450	2ch LVDS	21.7	404.2 × 330.0 × 15.0	1 850	Advanced Super V, Long-life LED backlight
	LQ190E1LW72					350		19.6	396.0 × 323.6 × 11.5	1 300	Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
	LQ190E1LX75T					350		19.6			Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit, Haze value 3%
	☆LQ190E1LX76					470		21.1			Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
51 [20.1]	LQ201U1LW31	1 600 × XYZ × 1 200	0.255 × 0.255	408.0 × 306.0	256 gray scale	1 000	2ch LVDS	25.7	436.0 × 335.0 × 20.4	2 400	Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit, Monochrome
	LQ201U1LW32	1 600 × RGB × 1 200			16.77 M	330					Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
59 [23.1]	LQ231U1LW32	1 600 × RGB × 1 200	0.294 × 0.294	470.4 × 352.8	16.77 M	500	2ch LVDS	65.5	530.0 × 431.5 × 23.9	4 500	Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
69 [27.0]	LQ270M1LX01	1 920 × RGB × 1 200	0.303 × 0.303	581.76 × 363.6	16.77 M	500	2ch LVDS	43.5	620.0 × 407.6 × 22.0	3 800	Advanced Super V, Long-life LED backlight

All products listed on this page are LED backlight models.

*1 Protrusions such as positioning bosses are not included.

Note: Please note that the specifications are subject to change without prior notice for product improvement.

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP. *RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



<For digital signage displays>

Display size (cm) ["]	Model No.	Dot format H × V (dot)	Pixel pitch H × V (mm)	Active area H × V (mm)	Display colors	Luminance (cd/m ²) (TYP.)	Interface	Outline dimensions*1 W × H × D (mm) (TYP.)	Weight (kg)	Remarks
176.56 [69.5]	LQ695D3LG21	1 920 × RGB × 1 080	0.802 × 0.802	1 538.88 × 865.62	1.07B 8-bit + 2-bit FRC	700	LVDS	1 566.0 × 901.8 × 27.0	26.5±1.5	Backlight type: edge-lit LED (built-in driver) SFR (60 Hz input–60 Hz output) Viewing angle (L/R / U/D): 176° / 176° Orientation: portrait / landscape
	LQ695D3LG02					350		1 559.4 × 893.0 × 27.5		
	LK695D3LA48				16.70 M 8-bit	450		1 566.0 × 901.8 × 29.6	26.0±1.0	Backlight type: edge-lit LED (built-in driver) SFR (60 Hz input–60 Hz output) Viewing angle (L/R / U/D): 176° / 176° Orientation: portrait / landscape
	LK695D3LA58					700				
	LQ695R3VG03	3 840 × RGB × 2 160	0.401 × 0.401		1.07B 8-bit + 2-bit FRC	330	V by One	1 559.4 × 893.0 × 27.5	26.0±1.5	Backlight type: edge-lit LED (built-in driver) SFR (60 Hz input–60 Hz output) Viewing angle (L/R / U/D): 176° / 176° Orientation: portrait / landscape
203.21 [80]	LK800D3LA28	1 920 × RGB × 1 080	0.9225 × 0.9225	1 771.20 × 996.30	1.07B 8-bit + 2-bit FRC	350	LVDS	1 820.2 × 1 045.3 × 34.4	34.0±1.0	Backlight type: edge-lit LED (built-in driver) DFR (60 Hz input–120 Hz output) Viewing angle (L/R / U/D): 176° / 176° Orientation: portrait / landscape
	LK800D3LA38					500				
	LK800D3LA48					700				
228.66 [90]	LQ900D3LA01	1 920 × RGB × 1 080	1.038 × 1.038	1 992.96 × 1 121.04	1.07B 8-bit + 2-bit FRC	500	LVDS	2 032.0 × 1 168.0 × 80.0	46.5±1.0	Backlight type: direct-lit LED (built-in driver) DFR (120 Hz input–120 Hz output) Viewing angle (L/R / U/D): 176° / 176° Orientation: portrait / landscape

*1 Excluding FPC for connection and other protruding parts.

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.
 Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP.
 *RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.
 Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

<For wearable & mobile terminal device (low power consumption LCD)>

Display size (cm) ["]	Model No.	Dot format H × V (dot)	Pixel pitch H × V (mm)	Active area H × V (mm)	Display colors	Luminance (cd/m ²) (TYP.)	Interface	Power consumption* ¹ (μW) (TYP.)	Outline dimensions* ² W × H × D (mm) (TYP.)	Weight (g) (MAX.)	Remarks
2.6 [1.03]	☆LS010B7DH04	128 × 128	0.145 × 0.145	18.56 × 18.56	B/W	No B/L	Serial	45	22.12 × 25.82 × 0.745	1.0	
2.7 [1.08]	★LS011B7DH03	160 × 68	0.158 × 0.158	25.28 × 10.744	B/W	No B/L	Serial	25	32.0 × 14.0 × 0.745	0.73	
3 [1.17]	LS012B7DD01	184 × 38	0.158 × 0.158	29.072 × 6.004	B/W	No B/L	Serial	189	35.1 × 11.0 × 0.741	0.6	
3 [1.19]	★LS012B7DD06	240 × RGB × 240	0.126 × 0.126	ø30.24	64-color	No B/L	6-bit parallel	33* ³	33.04 × 33.94 × 0.785	1.6	
3.2 [1.26]	LS013B7DH05	144 × 168	0.145 × 0.145	20.88 × 24.36	B/W	No B/L	Serial	35	24.68 × 30.00 × 0.745	1.1	
3.3 [1.28]	LS013B7DH03	128 × 128	0.180 × 0.180	23.04 × 23.04	B/W	No B/L	Serial	50	26.6 × 30.3 × 0.745	1.3	
4.6 [1.8]	★LS018B7DH02	230 × 303	0.12 × 0.12	27.6 × 36.36	B/W	No B/L	Serial	100	31.0 × 41.46 × 0.745	2.03	
6.9 [2.7]	LS027B7DH01	400 × 240	0.147 × 0.147	58.8 × 35.28	B/W	No B/L	Serial	175	62.8 × 42.82 × 1.65	11.0	
8.0 [3.16]	☆LS032B7DD02	336 × 536	0.127 × 0.127	42.672 × 68.072	B/W	No B/L	Serial	250	47.02 × 76.0 × 0.705	5.5	
11.2 [4.4]	LS044Q7DH01	320 × 240	0.280 × 0.280	89.6 × 67.2	B/W	No B/L	Serial	600	94.8 × 75.2 × 1.64	29.0	

*1 Data update mode (Display pattern: Vertical stripe display)

*2 Protrusion such as positioning bosses are not included.

*3 Data update mode (Display pattern: White display)

Note: Please note that the specifications are subject to change without prior notice for product improvement.

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the RoHS Directive*. For details, please contact SHARP.

*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.