

■LCD Modules

<For industrial appliances>

Display size (cm) ["]	Model No.	Dot format H × V (dot)	Pixel pitch H × V (mm)	Active area H × V (mm)	Display colors	Luminance (cd/m ²) (TYP.)	Interface	Power consumption (W) (TYP.)	Outline dimensions*1 W × H × D (mm) (TYP.)	Weight (g) (MAX.)	Remarks
8.8 [3.5]	LQ035Q3DG03	320 × RGB × 240	0.2205 × 0.2205	70.56 × 52.92	16.19 M	450	CMOS	0.8	76.9 × 63.9 × 4.7	TYP. 42	Long-life LED backlight
8.9 [3.5]	LQ035Q3DY01	240 × RGB × 320	0.2235 × 0.2235	53.64 × 71.52	260 k	600	CMOS	0.5	65.0 × 85.0 × 3.4	40	Advanced Super V, Low reflection technology
9.4 [3.7]	LS037V7DW05	480 × RGB × 640	0.117 × 0.117	56.16 × 74.88	16.77 M	250	CMOS	0.4	65.0 × 89.2 × 4.4	50	Advanced Super V, Transflective LCD, With resistive touch panel
	LS037V7DW06					300			65.0 × 89.2 × 3.6	38	Advanced Super V, Transflective LCD
11 [4.3]	LQ043T1DG38G	480 × 272 × RGB	0.198 × 0.198	95.04 × 53.856	16.77 M	300	CMOS	0.6	105.5 × 67.2 × 4.2	61	With resistive touch panel
	☆LQ043T1DG39G					360			105.5 × 67.2 × 3.1	46	(Mechanically compatible with DG38G in X,Y direction)
	LQ043Y1DY01					315			62.46 × 105.9 × 2.1	30	Advanced Super V, Low reflection technology
14 [5.7]	LQ057Q3DC03	320 × 240 × RGB	0.36 × 0.36	115.2 × 86.4	260 k	500	CMOS	2.5	144.0 × 104.6 × 12.3	210	Long-life LED backlight, Built-in LED backlight driver circuit
16 [6.4]	LQ064X3LW01	1 024 × RGB × 768	0.12675 × 0.12675	129.792 × 97.344	16.77 M	350	LVDS	5.3	153.4 × 122.0 × 9.9	TYP. 220	Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
18 [7.0]	LQ070Y3LW01	800 × 480 × RGB	0.1905 × 0.1905	152.4 × 91.44	16.19 M	380	LVDS	2.7	170.0 × 110.0 × 9.0	TYP. 175	Advanced Super V, Long-life LED backlight
20 [8.0]	☆LQ080Y3LW01	800 × RGB × 480	0.2175 × 0.2175	174.0 × 104.4	16.77 M	650	LVDS	4.6	191.8 × 120.7 × 7.25	280	Advanced Super V, Long-life LED backlight
21 [8.4]	LQ084V1DG43	640 × RGB × 480	0.267 × 0.267	170.88 × 128.16	260 k	370	CMOS	4.7	221.0 × 152.4 × 9.3	340	Long-life LED backlight, Built-in LED backlight driver circuit
	LQ084S3LG03	800 × RGB × 600	0.213 × 0.213	170.4 × 127.8	16.19 M	330	LVDS	4.1	199.5 × 154.0 × 11.6	320	Long-life LED backlight, Built-in LED backlight driver circuit
23 [9.1]	LQ091B1LW01	822 × RGB × 260	0.267 × 0.267	219.474 × 69.42	16.77 M	380	LVDS	6.8	240.0 × 86.0 × 10.0	230	Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
26 [10.1]	LQ101K1LY05	1 280 × RGB × 800	0.1695 × 0.1695	216.96 × 135.6	16.77 M	400	LVDS	4.2	230.7 × 152.5 × 8.7	270	Advanced Super V, Low reflection technology, Long-life LED backlight, Built-in LED backlight driver circuit
	LQ101W3LG01	1 024 × RGB × 600	0.2175 × 0.2088	222.72 × 125.28	260 k	350		5.1	235.3 × 143.0 × 7.9	350	Long-life LED backlight, Built-in LED backlight driver circuit
26 [10.4]	☆LQ104V1DG74	640 × RGB × 480	0.33 × 0.33		260 k	370	CMOS	4.5	227.3 × 177.5 × 10.0	460	Long-life LED backlight, Built-in LED backlight driver circuit
	LQ104V1DG81/LG81					450	CMOS/LVDS	5.6	246.5 × 179.3 × 12.5	TYP. 500	Long-life LED backlight, Built-in LED backlight driver circuit
	LQ104S1DG2C	800 × RGB × 600	0.264 × 0.264	211.2 × 158.4	260 k	350	CMOS	4.5	246.5 × 179.3 × 11.0	550	Long-life LED backlight, Built-in LED backlight driver circuit
	★LQ104S1LG74					450	LVDS	6.0	227.3 × 177.5 × 9.3	500	Long-life LED backlight, Built-in LED backlight driver circuit
	LQ104S1LG81				260 k	420	LVDS	6.1	246.5 × 179.3 × 12.5	500	Long-life LED backlight, Built-in LED backlight driver circuit

All products listed on this page are LED backlight models.

*1 Protrusions such as positioning bosses are not included.

Note: Please note that the specifications are subject to change without prior notice for product improvement.



■LCD Modules

<For industrial appliances> (cont'd)

Display size (cm) ["]	Model No.	Dot format H × V (dot)	Pixel pitch H × V (mm)	Active area H × V (mm)	Display colors	Lumi- nance (cd/m ²) (TYP.)	Interface	Power con- sumption (W) (TYP.)	Outline dimensions*1 W × H × D (mm) (TYP.)	Weight (g) (MAX.)	Remarks
31 [12.1]	LQ121S1DG81	800 × RGB × 600	0.3075 × 0.3075	246.0 × 184.5	260 k	450	CMOS	6.2	276.0 × 209.0 × 11.0	650	Long-life LED backlight, Built- in LED backlight driver circuit
	LQ121S1LG84				260 k	450	LVDS	5.1	276.0 × 209.0 × 9.1	600	Long-life LED backlight, Built- in LED backlight driver circuit
	LQ121S1LG86					1 500		12.9			Long-life LED backlight, Built- in LED backlight driver circuit
	LQ121K1LG52	1 280 × RGB × 800	0.204 × 0.204	261.1 × 163.2	16.19 M	430		6.0	278.0 × 184.0 × 8.6	550	Long-life LED backlight, Built-in LED backlight driver circuit
	LQ121K1LW56				16.77 M	320		5.2	278.0 × 184.0 × 10.2		Wide Viewing Angle Long-life LED backlight, Built- in LED backlight driver circuit
	LQ121K1LG58				16.19 M	700		5.8	278.0 × 184.0 × 8.6		Long-life LED backlight, Built- in LED backlight driver circuit
	LQ121X3LG02	1 024 × RGB × 768	0.240 × 0.240	245.8 × 184.3	260 k	1 200		9.7	259.0 × 205.0 × 7.5		
38 [15.0]	LQ150X1LG11	1 024 × RGB × 768	0.297 × 0.297	304.1 × 228.1	16.19 M	600	LVDS	8.2	331.6 × 254.7 × 9.3	950	Long-life LED backlight, Built- in LED backlight driver circuit
	LQ150X1LG91					350		6.8	326.5 × 253.5 × 9.6		Long-life LED backlight, Built- in LED backlight driver circuit
	LQ150X1LG96					1 050		14.8			Built-in LED backlight driver circuit
	LQ150X1LX92				16.19 M	270		10.0			Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit, Haze value 3%
	LQ150X1LX95					400					Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit, Haze value 3%
	LQ150X1LX96					500					Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit, Haze value 3%
	LQ150X1LX9K				16.19 M	400					Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit, Polarized sunglasses supported
	LQ150X1LW12				10 M	350		10.2	331.6 × 254.7 × 9.3		Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
	LQ150X1LW95				16.19 M	400		10.0	326.5 × 253.5 × 9.6		Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
	LQ150X1LW96					500					Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit

All products listed on this page are LED backlight models.

*1 Protrusions such as positioning bosses are not included.

Note: Please note that the specifications are subject to change without prior notice for product improvement.

■LCD Modules

<For industrial appliances> (cont'd)

Display size (cm) ["]	Model No.	Dot format H × V (dot)	Pixel pitch H × V (mm)	Active area H × V (mm)	Display colors	Luminance (cd/m ²) (TYP.)	Interface	Power consumption (W) (TYP.)	Outline dimensions*1 W × H × D (mm) (TYP.)	Weight (g) (MAX.)	Remarks
40 [15.6]	LQ156T3LW03	1 366 × RGB × 768	0.252 × 0.252	344.232 × 193.536	16.77 M	400	LVDS	16.9	363.8 × 215.9 × 10.8	950	Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
	LQ156M1LG21	1 920 × RGB × 1 080	0.17925 × 0.17925	344.16 × 193.59	16.19 M	300/350/400/600	2ch LVDS	13.6 (600cd/m ²)	370.0 × 217.0 × 9.3		Long-life LED backlight, Built-in LED backlight driver circuit, With brightness control switch
	LQ156M3LW01				16.77 M	400		17.9	363.8 × 215.9 × 10.8		Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
48 [19.0]	LQ190E1LW72	1 280 × RGB × 1 024	0.294 × 0.294	376.32 × 301.056	16.77 M	350	2ch LVDS	19.6	396.0 × 323.6 × 11.5	1 300	Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
	LQ190E1LX75T					350		19.6			Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit, Haze value 3%
	☆LQ190E1LX76					470		21.1			Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
51 [20.1]	LQ201U1LW31	1 600 × XYZ × 1 200	0.255 × 0.255	408.0 × 306.0	256 gray scale	1 000	2ch LVDS	25.7	436.0 × 335.0 × 20.4	2 400	Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit, Monochrome
	LQ201U1LW32	1 600 × RGB × 1 200			16.77 M	330					Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
59 [23.1]	LQ231U1LW32	1 600 × RGB × 1 200	0.294 × 0.294	470.4 × 352.8	16.77 M	500	2ch LVDS	65.5	530.0 × 431.5 × 23.9	4 500	Advanced Super V, Long-life LED backlight, Built-in LED backlight driver circuit
69 [27.0]	LQ270M1LX01	1 920 × RGB × 1 200	0.303 × 0.303	581.76 × 363.6	16.77 M	500	2ch LVDS	43.5	620.0 × 407.6 × 22.0	3 800	Advanced Super V, Long-life LED backlight
80 [31.5]	★LQ315D1VW11	3 840 × RGB × 2 160	0.18175 × 0.18175	697.92 × 392.58	1.07 B	700	V by One	(53.8)	734.8 × 430.0 × 26.5	6 000	Wide Viewing Angle Adobe RGB 100%

All products listed on this page are LED backlight models.

*1 Protrusions such as positioning bosses are not included.

Note: Please note that the specifications are subject to change without prior notice for product improvement.



<For digital signage displays>

Display size (cm) ["]	Model No.	Dot format H × V (dot)	Pixel pitch H × V (mm)	Active area H × V (mm)	Display colors	Luminance (cd/m ²) (TYP.)	Interface	Outline dimensions*1 W × H × D (mm) (TYP.)	Weight (kg)	Remarks
176.56 [69.5]	LQ695D3LG21	1 920 × RGB × 1 080	0.802 × 0.802	1 538.88 × 865.62	1.07B 8-bit + 2-bit FRC	700	LVDS	1 566.0 × 901.8 × 27.0	26.5±1.5	Backlight type: edge-lit LED (built-in driver) SFR (60 Hz input–60 Hz output) Viewing angle (L/R / U/D): 176° / 176° Orientation: portrait / landscape
	LQ695D3LG02					350		1 559.4 × 893.0 × 27.5		Backlight type: edge-lit LED DFR (120 Hz input–120 Hz output) Viewing angle (L/R / U/D): 176° / 176° Orientation: portrait / landscape
	LK695D3LA48				16.70 M 8-bit	450		1 566.0 × 901.8 × 29.6	26.0±1.0	Backlight type: edge-lit LED (built-in driver) SFR (60 Hz input–60 Hz output) Viewing angle (L/R / U/D): 176° / 176° Orientation: landscape
	LK695D3LA58					700				Backlight type: edge-lit LED (built-in driver) SFR (60 Hz input–60 Hz output) Viewing angle (L/R / U/D): 176° / 176° Orientation: portrait / landscape
	LQ695R3VG03	3 840 × RGB × 2 160	0.401 × 0.401		1.07B 8-bit + 2-bit FRC	330	V by One	1 559.4 × 893.0 × 27.5	27.5±1.5	Backlight type: edge-lit LED (built-in driver) SFR (60 Hz input–60 Hz output) Viewing angle (L/R / U/D): 176° / 176° Orientation: portrait / landscape
203.21 [80]	LK800D3LA28	1 920 × RGB × 1 080	0.9225 × 0.9225	1 771.20 × 996.30	1.07B 8-bit + 2-bit FRC	350	LVDS	1 820.2 × 1 045.3 × 34.4	34.0±1.0	Backlight type: edge-lit LED (built-in driver) DFR (60 Hz input–120 Hz output) Viewing angle (L/R / U/D): 176° / 176° Orientation: portrait / landscape
	LK800D3LA38					500				
	LK800D3LA48					700				
228.66 [90]	LQ900D3LA01	1 920 × RGB × 1 080	1.038 × 1.038	1 992.96 × 1 121.04	1.07B 8-bit + 2-bit FRC	500	LVDS	2 032.0 × 1 168.0 × 80.0	46.5±1.0	Backlight type: direct-lit LED (built-in driver) DFR (120 Hz input–120 Hz output) Viewing angle (L/R / U/D): 176° / 176° Orientation: portrait / landscape

*1 Excluding FPC for connection and other protruding parts.

<For wearable & mobile terminal device (low power consumption LCD)>

Display size (cm) ["]	Model No.	Dot format H × V (dot)	Pixel pitch H × V (mm)	Active area H × V (mm)	Display colors	Luminance (cd/m ²) (TYP.)	Interface	Power consumption* ¹ (μW) (TYP.)	Outline dimensions* ² W × H × D (mm) (TYP.)	Weight (g) (MAX.)	Remarks
2.6 [1.03]	LS010B7DH04	128 × 128	0.145 × 0.145	18.56 × 18.56	B/W	No B/L	Serial	45	22.12 × 25.82 × 0.745	1.0	
2.7 [1.08]	★LS011B7DH03	160 × 68	0.158 × 0.158	25.28 × 10.744	B/W	No B/L	Serial	25	32.00 × 14.00 × 0.745	0.73	
3 [1.17]	LS012B7DD01	184 × 38	0.158 × 0.158	29.072 × 6.004	B/W	No B/L	Serial	189	35.10 × 11.00 × 0.741	0.6	
3 [1.19]	☆LS012B7DD06	240 × RGB × 240	0.126 × 0.126	ø30.24	64-color	No B/L	6-bit parallel	33* ³	33.04 × 33.94 × 0.785	1.6	
3.2 [1.26]	LS013B7DH05	144 × 168	0.145 × 0.145	20.88 × 24.36	B/W	No B/L	Serial	35	24.68 × 30.00 × 0.745	1.1	
3.3 [1.28]	LS013B7DH03	128 × 128	0.180 × 0.180	23.04 × 23.04	B/W	No B/L	Serial	50	26.60 × 30.30 × 0.745	1.3	
4.6 [1.8]	★LS018B7DH02	230 × 303	0.12 × 0.12	27.6 × 36.36	B/W	No B/L	Serial	100	31.00 × 41.46 × 0.745	2.03	
6.9 [2.7]	LS027B7DH01	400 × 240	0.147 × 0.147	58.8 × 35.28	B/W	No B/L	Serial	175	62.8 × 42.82 × 1.65	11.0	
8.0 [3.16]	LS032B7DD02	336 × 536	0.127 × 0.127	42.672 × 68.072	B/W	No B/L	Serial	250	47.02 × 76.00 × 0.705	5.5	
11.2 [4.4]	LS044Q7DH01	320 × 240	0.280 × 0.280	89.6 × 67.2	B/W	No B/L	Serial	600	94.8 × 75.2 × 1.64	29.0	

*1 Data update mode (Display pattern: Vertical stripe display)

*2 Protrusion such as positioning bosses are not included.

*3 Data update mode (Display pattern: White display)

Note: Please note that the specifications are subject to change without prior notice for product improvement.