

NEOVIEW TECHNOLOGY INC.

Model Name	G070Y2-L01		
Mode	TN	Front View	Rear View
Resolution	800 x 480	coming soon	coming soon
Pixel Pitch(mm)	0.1905x0.1905		
Active Area(mm)	152.4x 91.44		
Outline(mm)	165x104x9.53		
Lux (nits)	500		
View Angle (U/D/R/L)	60/60/70/70		
Contrast Ratio	600:1		
Electrical Interface	LVDS		
Life time (min)	50000		
Operating Temperature	-30°C ~ 85°C		

Model Name	G070Y2-T02		
Mode	TN	Front View	Rear View
Resolution	800 x 480	coming soon	coming soon
Pixel Pitch(mm)	0.1905x0.1905		
Active Area(mm)	152.4x 91.44		
Outline(mm)	165x104x6.33		
Lux (nits)	500		
View Angle (U/D/R/L)	60/60/70/70		
Contrast Ratio	600:1		
Electrical Interface	TTL		
Life time (min)	50000		
Operating Temperature	-30°C ~ 85°C		

NEOVIEW TECHNOLOGY INC.

Model Name	G070Y3-T01		
Mode	TN	Front View	Rear View
Resolution	800 x 480	coming soon	coming soon
Pixel Pitch(mm)	0.195x0.1725		
Active Area(mm)	156 x 82.8		
Outline(mm)	168x94x6.35		
Lux (nits)	600		
View Angle (U/D/R/L)	60/60/70/70		
Contrast Ratio	650:1		
Electrical Interface	TTL		
Life time (min)	30000		
Operating Temperature	-30°C ~ 85°C		

Model Name	G070ACE-L01		
Mode	AAS	Front View	Rear View
Resolution	800 x 480	coming soon	coming soon
Pixel Pitch(mm)	0.1905x0.1905		
Active Area(mm)	152.4x 91.44		
Outline(mm)	168x107.7x6.0		
Lux (nits)	350		
View Angle (U/D/R/L)	89/89/89/89		
Contrast Ratio	800:1		
Electrical Interface	LVDS		
Life time (min)	50000		
Operating Temperature	0°C ~ 70°C		