



Figure similar

spare part SIMATIC S7-300, connection IM 361 in expansion rack for connection to central rack (IM360), supply voltage 24 V DC, with C-bus

Supply voltage			
Rated value (DC)			
● 24 V DC		Yes	
Input current			
from supply voltage L+, max.		500 mA	
Power loss			
Power loss, typ.		5 W	
Hardware configuration			
Number of interfaces per CPU, max.		3	
Dimensions			
Width		80 mm	
Height		125 mm	
Depth		120 mm	
Weights			
Weight, approx.		505 g	
Classifications			
		Version	Classification
	eClass	16	27-24-22-08
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	10	EC001423
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
	IDEA	4	3564
	UNSPSC	15	32-15-17-05
Approvals / Certificates			
General Product Approval			



[Manufacturer Declaration](#)



General Product Approval	EMV	For use in hazardous locations			
--------------------------	-----	--------------------------------	--	--	--

[Manufacturer Declaration](#)



[EM](#)



For use in hazardous locations			Maritime application		
--------------------------------	--	--	----------------------	--	--



[Miscellaneous](#)

[CCC-Ex](#)



Maritime application					
----------------------	--	--	--	--	--



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

last modified:

4/7/2025