

Mobile Shredder

JUST SHRED IT

IOWO

总质量31000kg

Contact Harden for professional shredding and recycling solutions.

no

HARDEN MACHINERY LTD. Address: XingDa Street, Torch Development Zone, Zhongshan city, China Email: info@hardenmachinery.com Tel: 0760-89935422 Web: www.harden-shredder.com





JUST SHRED IT

About Us

Harden Machinery Ltd. is a leading manufacturer of industrial shredder and waste disposal equipment in China. With a growing market and hundreds of successful cases we had built, Harden had became the most trustworthy brand in China, also it's being more popular worldwide. Thanks to rich experience and our strong R&D team, Harden always keeps advance in technologies.

Harden supplies competitive shredding machines worldwide, including single shaft shredder, double shaft shredder, quad shaft shredder, primary shredder and mobile shredder. We also offer a wide range of one-step solutions such as MRF system for MSW, SMP system for hazardous waste, shredding disposal system for organic waste, paper mill waste and bulky waste, etc.

Core Advantages of Harden

Professional Technologies Focus on shredding technologies from beginning to now

Trustworthy Brand 900+ successful projects / Wide recognition in market

1



High Reliability All parts in world brands / Advanced and mature designs

Aims the best ROI for customers

Batch production saves cost / High Durability Proven

2



Application





3 —

Tires

C&D waste

MSW



Green waste

Mattresses and Bulky waste Waste wood, board





Cars body

4



Product Features

- » VT-blade Profile Good performance (Energy savings up to 20%), . self-cleaning
- » Intelligent Driving System Automatic speed adjustment, Automatic reversing function
- » Humanized Design Accessibility, Easy to maintenance and less downtime
- » Excellent Mobility Almost can be everywhere and working for you









Power unit Diesel engine(kw/HP) 264/359 338/460 522/710 Electric motor(kw) 250 2×160 2×250 Shredding unit max 25rpm max 25rpm max 25rpm Shaft speed max 25rpm max 25rpm max 25rpm Shaft length 1750mm 2000mm 2500mm Dimensions 2500mm 2500mm L×W×H(Hook) 7m×2.4m×2.7m - - L×W×H(Track) 7.9m×2.5m×2.8m 8.5m×2.9m×3.2m 12.9m×3m×4m L×W×H(Electric motor) 7.4m×2.4m×2.7m 8m×2.5m×2.8m 9m×3m×3.3m Weight 1 - - - Hook 18t - - - Track 20t 25t 42t - Dietric 18t 20t 35t -			MS760	MS860	MS960
Electric motor (kw) 250 2×160 2×250 Shredding unit L ×W×H(Hook) 7m×2.4m×2.7m 8m×2.5m×2.8m 8m×2.5m×2.8m 9m×3m×3.3m <td></td> <td>Power unit</td> <td></td> <td></td> <td></td>		Power unit			
Shredding unitShaft speedmax 25rpmmax 25rpmShaft length1750mm2000mmDimensions2500mmL×W×H(Hook)7m×2.4m×2.7m-L×W×H(Track)7.9m×2.5m×2.8m8.5m×2.9m×3.2mL×W×H(Electric motor)7.4m×2.4m×2.7m8m×2.5m×2.8mWeight-Hook18t-Track20t25tElectric18t20tOptions35t		Diesel engine(kw/HP)	264/359	338/460	522/710
Shaft speedmax 25rpmmax 25rpmmax 25rpmShaft length1750mm2000mm2500mmDimensions </td <td></td> <td>Electric motor(kw)</td> <td>250</td> <td>2×160</td> <td>2×250</td>		Electric motor(kw)	250	2×160	2×250
Shaft length 1750mm 2000mm 2500mm Dimensions </td <td></td> <td>Shredding unit</td> <td></td> <td></td> <td></td>		Shredding unit			
Dimensions L×W×H(Hook) 7m×2.4m×2.7m - <t< td=""><td></td><td>Shaft speed</td><td>max 25rpm</td><td>max 25rpm</td><td>max 25rpm</td></t<>		Shaft speed	max 25rpm	max 25rpm	max 25rpm
L×W×H(Hook) 7m×2.4m×2.7m - - L×W×H(Track) 7.9m×2.5m×2.8m 8.5m×2.9m×3.2m 12.9m×3m×4m L×W×H(Electric motor) 7.4m×2.4m×2.7m 8m×2.5m×2.8m 9m×3m×3.3m Weight 18t - - Hook 18t - - Track 20t 25t 42t Electric 18t 20t 35t Options - - -		Shaft length	1750mm	2000mm	2500mm
L×W×H(Track) 7.9m×2.5m×2.8m 8.5m×2.9m×3.2m 12.9m×3m×4m L×W×H(Electric motor) 7.4m×2.4m×2.7m 8m×2.5m×2.8m 9m×3m×3.3m Weight - - Hook 18t - - Track 20t 25t 42t Electric 18t 20t 35t Options - - -		Dimensions			
L×W×H(Electric motor) 7.4m×2.4m×2.7m 8m×2.5m×2.8m 9m×3m×3.3m Weight -		L×W×H(Hook)	7m×2.4m×2.7m	-	-
WeightHook18tTrack20t20t25tElectric18tOptions		L×W×H(Track)	7.9m×2.5m×2.8m	8.5m×2.9m×3.2m	12.9m×3m×4m
Hook18t-Track20t25t42tElectric18t20t35tOptions		L×W×H(Electric motor)	7.4m×2.4m×2.7m	8m×2.5m×2.8m	9m×3m×3.3m
Track20t25t42tElectric18t20t35tOptions </td <td></td> <td>Weight</td> <td></td> <td></td> <td></td>		Weight			
Electric 18t 20t 35t Options		Hook	18t	-	-
Options		Track	20t	25t	42t
		Electric	18t	20t	35t
		Options			
Belt type magnetic separator, Water sprinking system,					
Track with rubber pads, Breaker bar, Special paint					

5

DISCHARGE BELT CONVEYOR Foldable and discharge height up to 4m

02

BELT TYPE MAGNETIC SEPARATOR

Adjustable height for effective ferrous metal separation.

03

SHREDDING UNIT

Different types of rotary blade available and using top-quality materials.

04

POEWR UNIT

Forceful and energy-efficient.

05

ELECTRIC CONTROL SYSTEM Intelligent, safe and easy to operate.

6