

Overview

The Tracer BPL series lithium battery MPPT solar charge controller combines solar charge controller and LED constant current driver into one unit which is ideal for solar LED Lighting, especially when dimmer function is needed. The advanced Maximum Power Point Tracking charging methods enables the system charging and discharging management to obtain the most radical optimization. Increase the system flexibility, yet lower down the system cost.




Features

- Adopt high quality components of ST,IR and Infineon, make sure product using lifespan
- Wide working environment temperature(-40℃~60℃)
- Apply to lead-acid battery and lithium battery
- Lithium battery self-activating and low temperature protection function
- Maximum conversion efficiency of 98%
- Advanced Maximum Power Point Tracking (MPPT) technology, with tracking efficiency no less than 99.5%
- Ultra-fast tracking speed and guaranteed tracking efficiency
- Accurately recognizing and tracking of multiple power points
- Lithium battery low temperature protection function
- Lithium battery limit current in low temperature
- Digital precision constant current control and the control accuracy are less than ±2%
- Intelligent power mode with 365-day lighting control technology
- Load reduce power automatically
- Maximum output efficiency of 96%
- PV and Load power limitation function
- The output current can be adjusted among the rated power and current range
- Monitoring and setting parameter via Mobile APP, PC Monitor setting software with RS485 communication interface.
- Use of standard Modbus communication protocol for RS485 bus connections, communication protocol compatibility much better
- Connecting the IOT(Internet of Things) module and Cloud Server monitoring software to realize remote monitoring of the multi-machine system
- The RS485 connector can provide power supply
- Aluminum housing for better cooling
- Real-time energy statistics function
- IP67 waterproof degree
- Long lifespan design, five years warranty

Electronic protections

- PV Short Circuit
- PV Reverse Polarity
- Battery Reverse Polarity
- Battery Over Voltage
- Battery Over Discharge
- Battery Overheating
- Libattery low temperature
- Load Short Circuit
- Controller Overheating
- High Voltage Transients



Solar Car




Solar Home




Solar Backpack



Solar Boat



Solar Street Light



Solar Power Generator

Technical Specifications

Model		Tracer2606BPL Tracer3906BPL Tracer5206BPL Tracer2610BPL Tracer3910BPL Tracer5210BPL					
Nominal system voltage	12/24VDC Auto(Lithium battery do not automatic identification system voltage)						
Battery input voltage range	8.5 ~ 32VDC						
Rated charge current ★	10A	15A	20A	10A	15A	20A	
Rated charge power	130W/12V 260W/24V	195W/12V 390W/24V	260W/12V 520W/24V	130W/12V 260W/24V	195W/12V 390W/24V	260W/12V 520W/24V	
Max. PV open circuit voltage	58V(at minimum operating environment temperature) 46V(at 25°C environment temperature)			95V(at minimum operating environment temperature) 92V(at 25°C environment temperature)			
MPP Voltage range	(Battery voltage+2V) ~ 36V			(Battery voltage+2V) ~ 72V			
Max. output current	3.3A	4.5A	6.6A	3.3A	4.5A	6.6A	
Max. output power	100W	130W	200W	100W	130W	200W	
Output voltage range	(Max. battery voltage+2V) ~ 58V			(Max. battery voltage+2V) ~ 80V			
Load open circuit voltage	58V			80V			
Load over voltage protection	63V			100V			
Maximum output efficiency	96%						
Output current control accuracy	≤2%						
Battery Type	Lead-acid battery: Sealed(Default) / Gel / Flooded/User; Lithium battery:LiFePO4/ Li-NiCoMn/User						
Lead-acid	Equalize Charging Voltage	Sealed :14.6V/Gel : No / Flooded:14.8V/User:9-17V (×2/24V)					
	Boost Charging Voltage	Sealed :14.4V/Gel : 14.2V/Flooded:14.6V/User:9-17V (×2/24V)					
	Float Charging Voltage	Sealed/Gel/Flooded:13.8V/User:9-17V (×2/24V)					
	Low Voltage Reconnect Voltage	Sealed/Gel/Flooded:12.6V/User:9-17V (×2/24V)					
	Low Voltage Disconnect Voltage	Sealed/Gel/Flooded:11.1V/User:9-17V (×2/24V)					
Lithium	Boost Charging Voltage	LiFePO4:14.5V/ Li-NiCoMn:12.5V / User:9-17V (×2/24V)					
	Low Voltage Reconnect Voltage	LiFePO4:12.8V / Li-NiCoMn:10.5V / User:9-17V (×2/24V)					
	Low Voltage Disconnect Voltage	LiFePO4:11.1V / Li-NiCoMn:9.3V / User:9-17V (×2/24V)					

Self-consumption	≤15mA/12V;≤22mA/24V					
Temperature compensation coefficient	-3mV/°C/2V(Lithium battery don't have temperature compensation coefficient)					
Communication	RS485 (RJ45)					
Working environment temperature	-40°C ~ +60°C					
Enclosure	IP67					
Overall dimension mm	124×89×30	150×93.5×32.7	153×105×52.1	124×89×30	150×93.5×32.7	153×105×52.1
Mounting hole size	Φ3.5mm					
Mounting dimension	88×76mm	120×83mm	120×94mm	88×76mm	120×83mm	120×94mm
Power cable	PV/BAT:14AWG(2.5mm ²) LOAD:18AWG(1.0mm ²)			PV/BAT:12AWG(4mm ²) LOAD:16AWG(1.5mm ²)		
Net weight	0.54kg	0.73kg	1.18kg	0.54kg	0.73kg	1.18kg

★The controller has the limit charge current function, the current can be set via the APP software and RC10.