

Threading Machine



SQ50

Capacity

- **Pipe:** ¼"-2" (8mm-50mm)
- **Bolt:** 12mm-45mm

Features

- Compact, light weight design.
- Powerful motor and transmission.
- Through die head oiling.
- Approved by CSA and CE standards.

Technical Specifications

- **Motor:** 1500W universal, 50/60Hz
- **Switch:** ON/OFF heavy duty switch, foot switch and FOR/OFF/REV switch optional
- **Spindle Speed:** 38 RPM
- **Front Chuck:** Hammer type with replaceable rocker action jaw inserts.
- **Rear Centering Device:** Cam action.
- **Oiling:** Through die head.
- **Oil Pump:** Self-priming constant flow.



standard dies
(HS standard)

Standard dies

- ½"-¾" universal HS dies set.
- 1"-2" universal HS dies set.



428 die head (standard)

Ordering Information

Catalog No.	Model No.	Description	Spindle Speed RPM	Pipe Threading Capacity		Rod Threading Capacity	N.W (kg)
				in.	mm.	metric	
302502	SQ50	110V, 50/60Hz	38	¼-2	8-50	M12-M45	67
302501	SQ50	220V, 50/60Hz	38	¼-2	8-50	M12-M45	67

* Die head and dies, order separately.



reinforced cutting wheel

Accessories

Catalog No.	Model No.	Description	N.W(kg)
	428	Die head, Quick-open (standard)	5.6
	425	Die head, Quick-open (optional)	5.3
	424	Die head, Self-open (optional)	5.8
40601009		reinforced cutting wheel	