

THREADING AND GROOVING

Threading Machine

SQ50E



Capacity

- **Pipe:** ¼"-2" (8mm-50mm)
- **Bolt:** 12mm-45mm

Features

- Heavy-duty proven performance.
- Fast transport and set-up.
- Self-Contained Oil System with adjustable flow control.
- Approved by CE standards.

Technical Specifications

- **Motor:** 1500W universal, 50/60Hz
- **Switch:** ON/OFF heavy duty switch, foot switch and FOR/OFF/REV switch are optional
- **Spindle Speed:** 38 RPM.
- **Front Chuck:** Hammer type with replaceable rocker action jaw inserts.
- **Rear Centering Device:** Cam action.
- **Oiling System:** Through die head, with intergral oil reservoir.
- **Pump:** Self-priming adjustable flow, gerotor pump.

Standard Dies

- ½"-¾" universal HS dies set.
- 1"-2" universal HS dies set.


Ordering Information

| Catalog No. | Model No. | Description | Spindle Speed RPM | Pipe Threading Capacity | | Rod Threading Capacity* | N.W (kg) |
|-------------|-----------|---------------|-------------------|-------------------------|------|-------------------------|----------|
| | | | | in. | mm. | metric | |
| 302312 | SQ50E | 110V, 50/60Hz | 38 | ¼-2 | 8-50 | M12-M45 | 75 |
| 302311 | SQ50E | 220V, 50/60Hz | 38 | ¼-2 | 8-50 | M12-M45 | 75 |


* Die head and dies, order separately.

Accessories

| Catalog No. | Model No. | Description | N.W(kg) |
|-------------|-----------|--|---------|
| | 425 | Die head, Quick-open (optional) | 5.3 |
| | 424 | Die head, Self-open (standard) | 5.8 |
| 11001004 | 651 | Pneumatic Folding Wheel Stand (optional) | 22 |
| 40601003 | | reinforced cutting wheel | |



standard dies (HS standard)



424 die head (standard)



reinforced cutting wheel



651 stand (optional)