

THREADING AND GROOVING

Threading Machine



SQ80C1

Capacity

- **Pipe:** ¼"-3" (8mm-80mm)
- **Bolt:** 12mm-45mm

Features


- Heavy-duty proven performance.
- Fast transport and set-up.
- Self-Contained Oil System with adjustable flow control.
- Approved by CE standards.

Technical Specifications

- **Motor:** 1500W universal, 50/60Hz
- **Switch:** ON/OFF heavy duty switch, foot switch and FOR/OFF/REV switch are optional
- **Spindle Speed:** 32 RPM.
- **Front Chuck:** Hammer type with replaceable rocker action jaw inserts.
- **Rear Centering Device:** Cam action.
- **Oiling System:** Through die head, with intergral oil reservoir.
- **Pump:** Self-priming adjustable flow, gerotor pump.



reinforced cutting wheel



standard dies
(HS standard)



432 die head



424 die head



651 stand (optional)

Standard Dies

- ½"-¾" universal HS dies set.
- 1"-2" universal HS dies set.
- 2 1/2"-3" universal HS dies set.

Ordering Information

Catalog No.	Model No.	Description	Spindle Speed RPM	Pipe Threading Capacity		Rod Threading Capacity	N.W (kg)
				in.	mm.	metric	
303301	SQ80C1	110V, 60Hz	32	¼-3	8-80	M12-M45	74
303302	SQ80C1	220V, 50Hz	32	¼-3	8-80	M12-M45	74

* Die head and dies, order separately.

Accessories

Catalog No.	Model No.	Description	N.W(kg)
	425	Die head, Quick-open (optional), ¼"-2"	5.3
	424	Die head, Self-open (standard), ¼"-2"	5.8
	432	Die head, Self-open 2½"-3"	6
11001004	651	Pneumatic Folding Wheel Stand (optional)	22
40601008		reinforced cutting wheel	