



QINGDAO TAIMEI NEW MATERIAL CO.,LTD

Product: PVC Coated Fabric

Application: Cocoa Drying Tarp,Scaffolding Enclosure / Building Tarps,Industrial Curtains

| MATERIAL DESCRIPTION | | | |
|-----------------------------|------------------|---------------|----------------------|
| ITEM | UNIT | RESULT | TEST STANDARD |
| Weight (+/-3%) | g/m ² | 300 | DIN EN ISO 2286-2 |
| Roll Width (Max) | m | 3.2/5.1 | |
| Bese Fabric | Type | Polyester | DIN 60001 |
| Yarn | Denier | 200*300 | DIN EN ISO 2060 |
| Thickness | mm | 0.3 | |
| Fabric Count | yarn/sq.inch | 18*12 | DIN EN 1049-2 |
| Type of Coating | Material | PVC | |

| PHYSICAL PROPERTIES | | | |
|----------------------------|---|---------------|--------------------|
| ITEM | UNIT | RESULT | Test Method |
| Weight (+/-3%) | g/m ² | 300 | DIN EN ISO 2286-2 |
| Tensile Strength-Warp | N/5cm | 500 | DIN53354 |
| Tensile Strength-Weft | N/5cm | 500 | DIN53354 |
| Tear Strength-Warp | N/5cm | 150 | DIN53363 |
| Tear Strength--Weft | N/5cm | 150 | DIN53363 |
| Coating Adhesiion | N/5cm | 50 | DIN53357 |
| Temp Resistance | °C | -30 to +70 | DIN EN 1876-2 |
| Fire Retardent | B1,B2 level is optional upon request | | |
| Treatment | UV treated; Acrylic Lacquered upon request. | | |
| Color | 16 standard color, and can be customized. | | |
| Printing Compatibility | Printing Ready | | |

Note: The technical specifications contained herein are believed to be reliable, but no representations, guarantees or warranties of any kind are made regarding their accuracy or suitability of the material for particular applications.