



**QINGDAO TAIMEI PRODUCTS CO.,LTD.**

Add.: No.6, Cuiling Rd, Qingdao, China

Tel.:+86-532-88615029 Email: info@taimeichina.com

<b>SPECIFICATION</b>			
<b>Item:</b> Tufflex-Tent Fabric750			
<b>Application:</b> Advertising Banner, Privacy Fencing			
<b>MATERIAL DESCRIPTION</b>			
<b>ITEM</b>	<b>UNIT</b>	<b>RESULT</b>	<b>TEST STANDARD</b>
Weight (+/-3%)	g/m <sup>2</sup>	750	DIN EN ISO 2286-2
Bese Fabric	Type	Polyester	DIN 60001
Yarn	Denier	1000*1000	DIN EN ISO 2060
Fabric Count	yarn/sq.inch	23*23	DIN EN 1049-2
Thickness	mm	0.58	
Roll Width (Max)	m	3.2	
Roll Length (Max)	m	20 - 800	
Surface Finishing	Material	PVC Coated	
<b>PHYSICAL PROPERTIES</b>			
<b>ITEM</b>	<b>UNIT</b>	<b>RESULT</b>	<b>Test Method</b>
Tensile Strength-Warp	N/5cm	3300	DIN53354
Tensile Strength-Weft	N/5cm	3200	DIN53354
Tear Strength-Warp	N/5cm	350	DIN53363
Tear Strength--Weft	N/5cm	320	DIN53363
Coating Adhesiion	N/5cm	100	DIN53357
Temp Resistance	°C	-30 to +70	DIN EN 1876-2
Fire Retardent	B1,B2 level is optional upon request		
Treatment	UV treated; Acrylic Lacquered upon request.		
Color	16 standard color, and can be customized.		
Printing Compatibility	Printing Ready		
Note: The technical specifications contained herein are believed to be reliable, but no representations, guarantees or warranties of any kind are made regarding their accuracy or suitability of the material for particular applications.			