



**QINGDAO TAIMEI PRODUCTS CO.,LTD.**

Add.: No.6, Cuiling Rd, Qingdao, China

Tel.:+86-532-88615029 Email: info@taimeichina.com

<b>SPECIFICATION</b>			
<b>Item: : Poly Tarps 65 to 80gsm</b>			
<b>MATERIAL DESCRIPTION</b>			
<b>ITEM</b>	<b>UNIT</b>	<b>RESULT</b>	<b>TEST STANDARD</b>
Weight (+/-3%)	g/m <sup>2</sup>	65-80	DIN EN ISO 2286-2
Bese Fabric	Type	HDPE	DIN 60001
Yarn	Denier	650-850	DIN EN ISO 2060
Fabric Count	yarn/sq.inch	8*8	DIN EN 1049-2
Thickness	mm	0.07-0.09	—
Roll Width (Max)	m		
Roll Length (Max)	m		
Surface Finishing	Material	LDPE+LLDPE	—
<b>PHYSICAL PROPERTIES</b>			
<b>ITEM</b>	<b>UNIT</b>	<b>RESULT</b>	<b>Test Method</b>
Tensile Strength-Warp	N/5cm	250-400	DIN53354
Tensile Strength-Weft	N/5cm	200-350	DIN53354
Temp Resistance	°C	-25 to +70	DIN EN 1876-2
Treatment	UV treated upon request.		
Color	16 standard color, and can be customized.		
<p>Note: The technical specifications contained herein are believed to be reliable, but no representations, guarantees or warranties of any kind are made regarding their accuracy or suitability of the material for particular applications.</p>			