



QINGDAO TAIMEI PRODUCTS CO.,LTD.

Add.: No.6, Cuiling Rd, Qingdao, China

Tel.:+86-532-88615029 Email: info@taimeichina.com

| SPECIFICATION | | | |
|--|---|---------------|----------------------|
| Item: : Poly Tarps 120 to 150gsm | | | |
| MATERIAL DESCRIPTION | | | |
| ITEM | UNIT | RESULT | TEST STANDARD |
| Weight (+/-3%) | g/m ² | 120-150 | DIN EN ISO 2286-2 |
| Bese Fabric | Type | HDPE | DIN 60001 |
| Yarn | Denier | 800-1000 | DIN EN ISO 2060 |
| Fabric Count | yarn/sq.inch | 12*12 | DIN EN 1049-2 |
| Thickness | mm | 0.11-0.16 | - |
| Roll Width (Max) | m | | |
| Roll Length (Max) | m | | |
| Surface Finishing | Material | LDPE+LLDPE | - |
| PHYSICAL PROPERTIES | | | |
| ITEM | UNIT | RESULT | Test Method |
| Tensile Strength-Warp | N/5cm | 500-800 | DIN53354 |
| Tensile Strength-Weft | N/5cm | 450-750 | DIN53354 |
| Temp Resistance | °C | -25 to +70 | DIN EN 1876-2 |
| Treatment | UV treated upon request. | | |
| Color | 16 standard color, and can be customized. | | |
| <p>Note: The technical specifications contained herein are believed to be reliable, but no representations, guarantees or warranties of any kind are made regarding their accuracy or suitability of the material for particular applications.</p> | | | |