



**QINGDAO TAIMEI PRODUCTS CO.,LTD.**

Add.: No.6, Cuiling Rd, Qingdao, China

Tel.:+86-532-88615029 Email: info@taimeichina.com

<b>SPECIFICATION</b>			
<b>Item: : Poly Tarps 150 to 200gsm</b>			
<b>MATERIAL DESCRIPTION</b>			
<b>ITEM</b>	<b>UNIT</b>	<b>RESULT</b>	<b>TEST STANDARD</b>
Weight (+/-3%)	g/m <sup>2</sup>	150-200	DIN EN ISO 2286-2
Bese Fabric	Type	HDPE	DIN 60001
Yarn	Denier	850-1150	DIN EN ISO 2060
Fabric Count	yarn/sq.inch	14*14	DIN EN 1049-2
Thickness	mm	0.16-0.22	—
Roll Width (Max)	m		
Roll Length (Max)	m		
Surface Finishing	Material	LDPE+LLDPE	—
<b>PHYSICAL PROPERTIES</b>			
<b>ITEM</b>	<b>UNIT</b>	<b>RESULT</b>	<b>Test Method</b>
Tensile Strength-Warp	N/5cm	750-1300	DIN53354
Tensile Strength-Weft	N/5cm	700-1250	DIN53354
Temp Resistance	°C	-25 to +70	DIN EN 1876-2
Treatment	UV treated upon request.		
Color	16 standard color, and can be customized.		
<p>Note: The technical specifications contained herein are believed to be reliable, but no representations, guarantees or warranties of any kind are made regarding their accuracy or suitability of the material for particular applications.</p>			