



QINGDAO TAIMEI PRODUCTS CO.,LTD.

Add.: No.6, Cuiling Rd, Qingdao, China

Tel.:+86-532-88615029 Email: info@taimeichina.com

SPECIFICATION			
Item: : Poly Tarps 200 to 300gsm			
MATERIAL DESCRIPTION			
ITEM	UNIT	RESULT	TEST STANDARD
Weight (+/-3%)	g/m ²	200-300	DIN EN ISO 2286-2
Bese Fabric	Type	HDPE	DIN 60001
Yarn	Denier	1000-1500	DIN EN ISO 2060
Fabric Count	yarn/sq.inch	16*16	DIN EN 1049-2
Thickness	mm	0.22-0.33	-
Roll Width (Max)	m		
Roll Length (Max)	m		
Surface Finishing	Material	LDPE+LLDPE	-
PHYSICAL PROPERTIES			
ITEM	UNIT	RESULT	Test Method
Tensile Strength-Warp	N/5cm	1200-1600	DIN53354
Tensile Strength-Weft	N/5cm	1100-1500	DIN53354
Temp Resistance	°C	-25 to +70	DIN EN 1876-2
Treatment	UV treated upon request.		
Color	16 standard color, and can be customized.		
<p>Note: The technical specifications contained herein are believed to be reliable, but no representations, guarantees or warranties of any kind are made regarding their accuracy or suitability of the material for particular applications.</p>			