



- ☐ PE TARPAULIN
- ☒ TRUCK COVER
- ☐ AWNING & CANOPY
- ☐ MEMBRANE STRUCTURE
- ☐ PARTY TENT
- ☐ WATER TANK



PVC Tarpaulin

QINGDAO TAIMEI PRODUCTS CO., LTD


www.taimeichina.com www.plastuf.com

TRUCK COVER & SIDE CURTAIN



Coated Tarpaulin for Truck Cover

- Hot-melt Coating technology (Semi-coating).
- Good peeling strength for welding.
- Outstanding tearing strength.
- Flame retardant character. (optional)
- Anti ultraviolet treatment (UV). (optional)
- Acrylic treatment (optional).



Truck Cover Material								
DATA SHEET								
Coating Material		PVC	PVC	PVC	PVC	PVC	PVC	PVC
Finish		Glossy/Matt	Glossy/Matt	Glossy/Matt	Glossy/Matt	Glossy/Matt	Glossy/Matt	Glossy/Matt
Width	DIN EN ISO 2286-1	1m-3.2m	1m-3.2m	1m-3.2m	1m-3.2m	1m-3.2m	1m-3.2m	1m-3.2m
Weight	DIN EN ISO 2286-2	500gsm	500gsm	610gsm	680gsm	750gsm	750gsm	900gsm
Yarn Construction	Polyester	1000Dx1000D D 9x9	1000Dx1000D 18x18	1000Dx1000D 20x20	1000Dx1000D 20x20	1300Dx1300D 18x18	1000Dx1000D 23x23	1000Dx1000D 30x30
Tensile Strength	(DIN53354)	1200/1100 N/5cm	2100/1950 N/5cm	2500/2300 N/5cm	2500/2300 N/5cm	2700/2500 N/5cm	2900/2700 N/5cm	3900/3700 N/5cm
Tear Strength	(DIN53363)	250/200 N/5cm	250/200 N/5cm	300/250 N/5cm	300/250 N/5cm	350/300 N/5cm	370/320 N/5cm	600/550 N/5cm
Coating Adhesion	(DIN53357)	40 N/5cm	80 N/5cm	100 N/5cm	100 N/5cm	100 N/5cm	100 N/5cm	120 N/5cm
Temperature	from -30°C to 70°C							
Flame Retardant	B1, B2, M1, M2, NFPA-701, CAPI-84 Optional							
Surface Treatment	Acrylic or PVDF Optional							
Other Optional	Ecofriendly, UV, Anti-Mildew, Aging Resistance, Cold Resistance, Optional							
To be Customized	Color, Softness, and other details							

Canvas Tarpaulin for Truck Cover



*We can customize any size or order.
Please call for special customization options

Side Curtain for Truck Cover



Side Curtain Material	
Specification	20x20; 15x15 per inch (plain weave)
Yarn	1000x1000 D
Type of Coating	PVC coated on both sides
Weight	680gsm; 900gsm
Width	Up to 3.2m
Tensile Strength	3000/2800 N/5CM; 4000/3800 N/5CM
Tear strength	300/300N/5CM; 550/500N/5CM
Adhesion Strength	100N/5CM
Yarn	1000x1000 D
Low Temperature-No Crack At	-30°C to +70°C

Your logo also can be printed on the material

Colors Available:



For further information, please contact: info@taimeichina.com



QINGDAO TAIMEI PRODUCTS CO., LTD.

Add.: No.6, Cuiling, Rd, Qingdao, China

Tel.: +86-532-88915029 / 88915092

website: www.taimeichina.com

Visit our website

