



# OUTDOOR SHADE & COVERING MATERIAL PROVIDER



Qingdao Taimel Products Co., Ltd  
[www.taimeichina.com](http://www.taimeichina.com)



# CONTENTS

**PE TARPAULIN**



**WEED BARRIER**



**SHADE NET**



**WEED MAT**



**TENT FABRIC**



**TRUCK COVER**



**WATER TANK**



**GEOMEMBRANE**



**PITCH COVER**



**AWNING FABRIC**



**PRIVACY FENCE**



**GREENHOUSE FILM**



**SHADE SAIL**



**TENSILE STRUCTURE**



**PP WOVEN BAG**



**GEOTEXTILE**





- ☒ PE TARPAULIN
- ☐ TRUCK COVER
- ☐ AWNING & CANOPY
- ☐ MEMBRANE STRUCTURE
- ☐ PARTY TENT
- ☐ WATER TANK



# Poly Tarpaulin

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.plastuf.com](http://www.plastuf.com)



# POLY TARPAULIN



## PE Tarpaulin

PE Tarps are perfect to protect exposed objects / areas in need of cover & protection. Strong, flexible, water resistant and waterproof, it made from the highest material available.

DENIER	MESH / SQ.INCH	WEIGHT
600D	6X6	50-60GSM
700-750D	7X6	60-70GSM
700-750D	7X7	80GSM
800-850D	8X8	90GSM
850-900D	10X8	100GSM
950-1000D	10X10	110-140GSM
1000D	12X12	140-150GSM
1000D	12X14	160-200GSM
1100-1500D	16X16	240-300GSM

VARIOUS  
COLORS  
AVAILABLE  
UPON  
REQUEST



- Waterproof
- Durable
- Resistant up to -20°C
- UV or FR Protected
- Eyelets every meter
- Tear-Resistant Material



**Swimming Pool Cover**

80gsm - 140gsm



**General Cover**

40gsm - 400gsm



**Scaffolding Sheet**

85gsm - 200gsm



**Camouflage Tarpaulin**

70gsm - 160gsm



**PE Insulated Tarpaulin**

80gsm - 300gsm

For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)



QINGDAO TAIMEI PRODUCTS CO.,LTD.

Add.: No.6, Cuijing, Rd, Qingdao, China

Tel.: +86-532-88915029 / 88915092

website: [www.taimeichina.com](http://www.taimeichina.com)

Visit our website





- ☒ PE TARPAULIN
- ☐ TRUCK COVER
- ☐ AWNING & CANOPY
- ☐ MEMBRANE STRUCTURE
- ☐ PARTY TENT
- ☐ WATER TANK



## Pitch Cover

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.plastuf.com](http://www.plastuf.com)



# PLAYGROUND COVER



## Cricket Flat Sheet Rain Cover



### Tarpaulin for Pitch Covers

Cricket pitch covers are manufactured from the highest quality lightweight woven polyethylene with a high tear strength; ideal for covering turf cricket wickets.

The cover fabric is extremely strong, translucent and breathable, which importantly allows light and air to pass through, protecting it from the rain whilst allowing vapour to escape ensuring the grass plant continues to grow underneath.



- Can be manufactured to any size
- Lightweight = safer to use and handle = less labour required for handling = lower operational costs
- Translucent – healthier plant when covered – cover can stay on for long periods
- Breathable – good air circulation & reduces 'sweating'
- Strength – guarantees on handles eyelets & seams – reduced chance of tearing/ripping

For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)



QINGDAO TAIMEI PRODUCTS CO., LTD.

Add.: No.6, Cuiling, Rd, Qingdao, China

Tel.: +86-532-88915029 / 88915092


website: [www.taimeichina.com](http://www.taimeichina.com)

Visit our website





- ☒ AGRICULTURE NET
- ☐ SUN SHADE SAIL
- ☐ SCREEN FENCE
- ☐ GREENHOUSE FILM



# Plastic Netting

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.goldenthread.com](http://www.goldenthread.com)




# AGRICULTURE NETTING



## Agriculture Shade Cloth



30% Shade Rate



30% Shade Rate



50% Shade Rate



70% Shade Rate



70% Shade Rate





80% Shade Rate

## Crop Protection Netting



Crop protection netting is designed to keep out even the most determined of pests.



These crop protection fabrics can be used in a range of commercial applications including greenhouses, hot houses, shade houses, crop tops and aquaculture cultivation.

## Bird Net & Pest Control Insect Net



Various kind of meshes to optimise the different harvesting methods of crops and orchards.



### CUSTOM

\*Available in different weights, several mesh sizes



Visit our website



For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)



QINGDAO TAIMEI PRODUCTS CO.,LTD.

Add.: No.6, Cuiling, Rd, Qingdao, China

Tel.: +86-532-88915029 / 88915092

website: [www.taimeichina.com](http://www.taimeichina.com)



- ☐ AGRICULTURE NET
- ☒ SUN SHADE SAIL
- ☐ SCREEN FENCE
- ☐ GREENHOUSE FILM




# Plastic Netting

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)   [www.goldenthread.com](http://www.goldenthread.com)





## Sun Shade Sail

Sun Shade Sail is made of polyethylene (HDPE) material by adding UV stabilizers and anti-oxidants. Lightweight and foldable design making you outdoor living spaces more comfortable.

### Sun Shade Sail

Material	100% new material (HDPE)
Weight	160gsm~360gsm
Shape	Triangle, Square, Rectangle
Color	According to Customer's Request

- Includes the tension mounted steel D-rings which are double stitched into the corners
- Each corner of the shade sail has metal hooks and it takes minutes to set
- Effective harmful UV blocking
- The fabric enables cool air to penetrate the shade sail, offering an airy, comfortable, and well-ventilated space.

### Color Range



Triangle Shape



Square Shape

### CUSTOM

\*We can customize any size or order. Please call for special customization options

For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)







- ☐ AGRICULTURE NET
- ☐ SUN SHADE SAIL
- ☒ SCREEN FENCE
- ☐ GREENHOUSE FILM



# Plastic Netting

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.goldenthread.com](http://www.goldenthread.com)




# SCREEN FENCE



## Screen Fence

Privacy screen fence netting is made from high density polyethylene (HDPE) with UV inhibitors for maximum life expectancy.

- 3-year warranty
- Weather Resistant and breathable
- Many fabrics and colors to choose from



## Balcony Net

Material	100% new material (HDPE)
Weight	180gsm or by requirements
Size	0.9m*5m or by requirements
Type	Warp knitted

- Includes quality soft white rope for attaching net.
- HDPE polyethylene mesh lets the breeze flow through so you stay cool
- Keep your outdoor life more private



## Printed Fence Screen

*More color matching  
According to your request color  
collocation*



***Your logo or graphic  
printed in full color***

For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)



QINGDAO TAIMEI PRODUCTS CO.,LTD.

Add.: No.6, Cuiling, Rd, Qingdao, China

Tel.: +86-532-88915029 / 88915092 website: [www.taimeichina.com](http://www.taimeichina.com)

Visit our website







- ☐ PE TARPAULIN
- ☒ TRUCK COVER
- ☐ AWNING & CANOPY
- ☐ MEMBRANE STRUCTURE
- ☐ PARTY TENT
- ☐ WATER TANK



# PVC Tarpaulin

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.plastuf.com](http://www.plastuf.com)




# TRUCK COVER & SIDE CURTAIN



## Coated Tarpaulin for Truck Cover

- Hot-melt Coating technology (Semi-coating).
- Good peeling strength for welding.
- Outstanding tearing strength.
- Flame retardant character. (optional)
- Anti ultraviolet treatment (UV). (optional)
- Acrylic treatment (optional).



Truck Cover Material								
DATA SHEET								
Coating Material		PVC	PVC	PVC	PVC	PVC	PVC	PVC
Finish		Glossy/Matt	Glossy/Matt	Glossy/Matt	Glossy/Matt	Glossy/Matt	Glossy/Matt	Glossy/Matt
Width	DIN EN ISO 2286-1	1m~3.2m	1m~3.2m	1m~3.2m	1m~3.2m	1m~3.2m	1m~3.2m	1m~3.2m
Weight	DIN EN ISO 2286-2	500gsm	500gsm	610gsm	680gsm	750gsm	750gsm	900gsm
Yarn Construction	Polyester	1000Dx1000D D 9x9	1000Dx1000D 18x18	1000Dx1000D 20x20	1000Dx1000D 20x20	1300Dx1300D 18x18	1000Dx1000D 23x23	1000Dx1000D 30x30
Tensile Strength	(DIN53354)	1200/1100 N/5cm	2100/1950 N/5cm	2500/2300 N/5cm	2500/2300 N/5cm	2700/2500 N/5cm	2900/2700 N/5cm	3900/3700 N/5cm
Tear Strength	(DIN53363)	250/200 N/5cm	250/200 N/5cm	300/250 N/5cm	300/250 N/5cm	350/300 N/5cm	370/320 N/5cm	600/550 N/5cm
Coating Adhesion	(DIN53357)	40 N/5cm	80 N/5cm	100 N/5cm	100 N/5cm	100 N/5cm	100 N/5cm	120 N/5cm
Temperature	from -30°C to 70°C							
Flame Retardant	B1, B2, M1, M2, NFPA-701, CAPI-84 Optional							
Surface Treatment	Acrylic or PVDF Optional							
Other Optional	Ecofriendly, UV, Anti-Mildew, Aging Resistance, Cold Resistance, Optional							
To be Customized	Color, Softness, and other details							

## Canvas Tarpaulin for Truck Cover



**\*We can customize any size or order.**  
Please call for special customization options

## Side Curtain for Truck Cover



Side Curtain Material	
Specification	20x20; 15x15 per inch (plain weave)
Yarn	1000x1000 D
Type of Coating	PVC coated on both sides
Weight	680gsm; 900gsm
Width	Up to 3.2m
Tensile Strength	3000/2800 N/5CM; 4000/3800 N/5CM
Tear strength	300/300N/5CM; 550/500N/5CM
Adhesion Strength	100N/5CM
Yarn	1000x1000 D
Low Temperature-No Crack At	-30°C to +70°C

**Your logo also can be printed on the material**

### Colors Available:



For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)



QINGDAO TAIMEI PRODUCTS CO., LTD.

Add.: No.6, Cuiling, Rd, Qingdao, China

Tel.: +86-532-88915029 / 88915092

website: [www.taimeichina.com](http://www.taimeichina.com)

Visit our website







- ☐ HAND & THROW TARP
- ☐ FLATBED TARP
- ☐ SIDE CURTAIN
- ☐ DUMP TRUCK TARP
- ☐ TRAILER TARP
- ☒ CARGO NET



## TRUCK COVER & CARGO NET

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com) [www.covertac.com](http://www.covertac.com)




# CARGO CONTROL NETS



## Dump Truck Mesh Tarps


Woven from poly fibers that are coated with PVC resin, these tarps are designed to hold up under recurring and rugged usage. The mesh weave allows air to flow through the tarp, eliminating wind resistance that could cause tears or abrasions. Evenly spaced, rust-proof grommets on the end allow easy tie down and double needle lock stitching assures the strength and durability needed to secure and protect your load. Mesh tarps are best suited for hauling rock, sand, debris, plants, and other loads that need protection but do not require 100% waterproof or windproof conditions.



## Trailer Mesh Tarp



## Cargo Control Net



## Cargo Mesh



For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)



QINGDAO TAIMEI PRODUCTS CO., LTD.

Add.: No.6, Cuiling, Rd, Qingdao, China

Tel.: +86-532-88915029 / 88915092 website: [www.taimeichina.com](http://www.taimeichina.com)

Visit our website





- ☐ HAND & THROW TARP
- ☒ FLATBED TARP
- ☐ SIDE CURTAIN
- ☐ DUMP TRUCK TARP
- ☒ TRAILER TARP
- ☐ CARGO NET

## FLATBED TARP



## TRUCK COVER & CARGO NET

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com) [www.covertac.com](http://www.covertac.com)



# FLATBED TARPS & TRAILER TARP



## Lumber Tarp & Steel Tarp for Truck

Flatbed tarps are essential tools for safely and effectively covering loads on flatbeds, semis, and hotshot trailers. Cargo is often heavy, misshapen, or sensitive to weather, so truckers often struggle to adequately and safely cover their load. We offer a variety of flatbed tarps for sale, including steel tarps, lumber tarps, coil tarps, smoke tarps, and box tarps. Every vinyl tarp features reinforced D rings to withstand tight strapping. They are completely waterproof as well as heat, tear, and UV resistant.



## Dump Truck Tarp



## Side Curtain for Truck Cover



## Trailer Tarp



For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)

**Taimei**

QINGDAO TAIMEI PRODUCTS CO., LTD.

Add.: No.6, Cuiling, Rd, Qingdao, China

Tel.: +86-532-88915029 / 88915092 website: [www.taimeichina.com](http://www.taimeichina.com)

Visit our website







- ☐ PE TARPAULIN
- ☐ TRUCK COVER
- ☒ AWNING & CANOPY
- ☐ MEMBRANE STRUCTURE
- ☐ PARTY TENT
- ☐ WATER TANK



## PVC COATED FABRIC

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.plastuf.com](http://www.plastuf.com)



# AWNING & CANOPY FABRIC



## Outdoor Shade Solutions !

### Striped PVC Tarpaulin for Sunshade Awning & Canopy

Striped PVC Fabric

DATA SHEET							
Coating Material		PVC	PVC	PVC	PVC	PVC	PVC
Finish		Glossy/Matt	Glossy/Matt	Glossy/Matt	Glossy/Matt	Glossy/Matt	Glossy/Matt
Width	DIN EN ISO 2286-1	1m~3.2m	1m~3.2m	1m~3.2m	1m~3.2m	1m~3.2m	1m~3.2m
Weight	DIN EN ISO 2286-2	400gsm	500gsm	500gsm	500gsm	500gsm	680gsm
Yarn Construction	Polyester	300Dx500D 18x12	500Dx500D 9x9	500Dx500D 18x17	840Dx840D 9x9	1000Dx1000D 9x9	1000Dx1000D 20x20
Tensile Strength	(DIN53354)	450/400 N/5cm	450/400 N/5cm	700/600 N/5cm	700/600 N/5cm	1200/1100 N/5cm	2500/2300 N/5cm
Tear Strength	(DIN53363)	80/70 N/5cm	120/110 N/5cm	150/140 N/5cm	150/140 N/5cm	250/200 N/5cm	300/250 N/5cm
Coating Adhesion	(DIN53357)	20 N/5cm	40 N/5cm	40 N/5cm	40 N/5cm	40 N/5cm	100 N/5cm
Temperature	from -30°C to 70°C						
Flame Retardant	B1, B2, M1, M2, NFPA-701, CAPI-84 Optional						
Surface Treatment	Acrylic or PVDF Optional						
Other Optional	Ecofriendly, UV, Anti-Mildew, Aging Resistance, Cold Resistance, Optional						
To be Customized	Color, Softness, and other details						





#### Striped PVC Tarpaulin Features:

- Good peeling strength for welding
- Outstanding tearing strength
- Flame retardant
- Flexible
- High strength

#### CUSTOM

\*Various color pattern, one side or double sides color striped



For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)



QINGDAO TAIMEI PRODUCTS CO.,LTD.

Add.: No.6, Cuiling, Rd, Qingdao, China


Tel.: +86-532-88915029 / 88915092 website: [www.taimeichina.com](http://www.taimeichina.com)

Visit our website





- ☐ PE TARPAULIN
- ☐ TRUCK COVER
- ☐ AWNING & CANOPY
- ☒ MEMBRANE STRUCTURE
- ☐ PARTY TENT FABRIC
- ☐ WATER TANK



# PVC COATED FABRIC

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.plastuf.com](http://www.plastuf.com)



## Membrane Structure




*Create your own custom  
shading and  
all-weather canopies.*

### Tensile Membrane Structure

Yarn	1000*1000D 1300D*1300D
Type of Coating	PVC coated on both sides
Weight	1100g/m <sup>2</sup> ; 1400g/m <sup>2</sup> ; 900g/m <sup>2</sup> ; 1050g/m <sup>2</sup>
Width	UP TO 3.2M
Tensile strength	5500/5200 N/5CM; 7200/7000 N/5CM; 4200/3900 N/5CM; 4500/4200 N/5CM; 4800/4400 N/5CM
Tear strength	650/550N/5CM; 750/700N/5CM; 550/500N/5CM; 600/500N/5CM; 500/450N/5CM
Adhesion Strength	120N/5CM; 160N/5CM

- Knife Coated technology
- Good strength, good flexibility and adhesion strength
- Outstanding tearing strength for welding
- UV resistant , FR
- Cold resistant, Anti-Mildew
- Lacquered are available as requests
- Color, weight can be customized



For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)





- ☐ PE TARPAULIN
- ☐ TRUCK COVER
- ☐ AWNING & CANOPY
- ☐ MEMBRANE STRUCTURE
- ☒ PARTY TENT FABRIC
- ☐ WATER TANK



# PVC COATED FABRIC

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.plastuf.com](http://www.plastuf.com)



# TENT FABRIC & CURTAINS



## PVC Fabric for Party Tent



PVC Party Tents provide a flexible and highly durable solution for parties, events, and exhibitions. Our tent fabric made of heavy duty plastic tarpaulin sheet.

### PVC Party Tent

Yarn	1000*1000D
Type of Coating	PVC coated on both sides
Weight	650g/m <sup>2</sup> ; 700g/m <sup>2</sup> ; 750g/m <sup>2</sup> ; 800g/m <sup>2</sup> ; 850g/m <sup>2</sup>
Width	UP TO 3.2M
Tensile strength	3300/3200 N/5CM; 3400/3300 N/5CM; 3500/3400 N/5CM; 3000/2900 N/5CM
Tear strength	350/320N/5CM; 360/340N/5CM
Adhesion Strength	100N/5CM; 90N/5CM
Low Temperature-No Crack At	-30°C to +70°C




**We offers  
a complete line of  
Tarps, making it easy to  
choose one that is right  
for any application!**



## Industrial Curtains

PVC Industrial curtains are a multipurpose solution that can partition off work areas from a variety of elements including noise, odor, sound, sight and other distractions that may inhibit or endanger workflow.



- Eliminates costly brick and mortar permanent type walls
- Quickly creates privacy areas
- Improve working conditions
- Easily slides out of the way when not needed
- Helps to control contaminants, temperature, odors, sound and light

**For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)**



QINGDAO TAIMEI PRODUCTS CO.,LTD.

Add.: No.6, Cuiling, Rd, Qingdao, China

Tel.: +86-532-88915029 / 88915092

website: [www.taimeichina.com](http://www.taimeichina.com)

Visit our website





- ☐ PE TARPAULIN
- ☐ TRUCK COVER
- ☐ AWNING & CANOPY
- ☐ MEMBRANE STRUCTURE
- ☐ PARTY TENT
- ☒ WATER TANK



# PVC Tarpaulin


QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.plastuf.com](http://www.plastuf.com)



## PVC Water Storage Tank

Water storage tank is made by PVC coated fabric, size from 250L to 500,000 L, which widely used for water and rain collection. The water tank can be used for many times and it can be placed in the outdoor to storage the bulk liquids.



### Accessories



### Application:

- Temporary Storage
- Rainfall Collection
- Residential and Public Storage of Water
- Defense Water Storage Applications
- Emergency Storage and Relief Irrigation
- Test bridge maximum load
- Fire fighting in forest



### PVC Water Tank

Capacity	Thicnkness	Size
250 liters	0.7 mm	1m*0.85m*0.3m
500 liters	0.7 mm	1.7m*0.85m*0.35m
1,000 liters	0.7 mm	2m*1.3m*0.4m
2,000 liters	0.7 mm	2.3m*1.8m*0.5m
3,000 liters	0.7 mm	2.8m*1.8m*0.6m
5,000 liters	0.7 mm	2.8m*2.8m*0.65m
10,000 liters	0.8 mm	3.85m*3.85m*0.7m
20,000 liters	0.9 mm	6.8m*3.8m*0.8m
30,000 liters	0.9 mm	6.6m*5.8m*0.8m
50,000 liters	0.9 mm	8.6m*7.3m*0.8m
70,000 liters	1.2 mm	8.9m*8.8m*0.9m
100,000 liters	1.2 mm	13m*7.8m*1m
200,000 liters	1.2 mm	17m*11.7m*1.1m
300,000 liters	1.5 mm	19m*14.6*1.1m
400,000 liters	1.5 mm	19m*17.6*1.2m
500,000 liters	1.5 mm	24m*17.6m*1.2m

### CUSTOM

\*We can customize any size or order. Please call for special customization options

For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)







A division of TAIMEI Group

- ☒ **WOVEN FABRIC**
- ☐ **NON-WOVEN WEEDMAT**
- ☐ **NON-WOVEN BLANKET**
- ☐ **SILT FENCE**
- ☐ **GEO-TEXTILE**



# Landscape Fabric

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.teratuf.com](http://www.teratuf.com)



# LANDSCAPE FABRIC



LANDSCAPE FABRIC IS THE SAFE AND EASY SOLUTION TO PERMANENT WEED CONTROL, ALSO NAMED WEED MAT

**Weed Mat** is "UV" protected fabric which allows air, water and nutrients to reach the plants roots while keeping the sunlight out, which prevents weed growth.

## FEATURES:

- Blocks Weeds Without Using Chemicals
- Saves Times - No More Pulling Weeds
- Allow Water, Air & Nutrients to reach to the soil, save water.
- Enhances plant growth.
- Prevents mulch Decay.



## Woven Weed Mat (Weed Barrier)

Woven weed mat is able to resist tearing, puncturing and weed penetration. It's very easy to install with the plastic or metal pins. Also, it is durable and most economic way for weed control

**Pre-Perforated Fabric Available!!!**

## Specification

**Material:** 100% Polypropylene, with UV Treated

**Lifespan:** 3 years to 6 years (Depend on the thickness)

**Width:** 0.2m~5m

**Length:** 10m~500m/roll

**Weight:** 60gsm~200gsm

**Mesh Size:** 10x10, 10x12, 11x11, 12x12, 14x14, 22x12

**Water Permeability:** 6L-22L/(S.SQ.M)

**We offer different kinds of woven weed control fabrics to suit all applications.**

### 6 Years Black Color Fabric:

We use the special famular during production to make it workable for 6 years

### High Water Permeability Fabric: (SULZER & WaterJet Loom Machine Available)

We could make extremely high water permeability with less light penetration

### White Color Fabric for In-door/Greenhouse Ground Cover:

White Color is usually used in applications where light reflection is desired.

### Ultra UV Black Color Fabric:

100 gsm with UV treated for max 5 years.

### Economic Black Color Fabric:

65 gsm with UV Treated for one season usage.

**ALL LANDSCAPE FABRICS ARE AVAILABLE IN BULK SIZES AND ROLLS**

For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)

**Taimei**

QINGDAO TAIMEI PRODUCTS CO.,LTD.

Add.: No.6, Cuiling, Rd, Qingdao, China

Tel.: +86-532-88915029 / 88915092 website: [www.taimeichina.com](http://www.taimeichina.com)

Visit our website







A division of TAIMEI Group

- ☐ WOVEN FABRIC
- ☒ NON-WOVEN WEEDMAT
- ☐ NON-WOVEN BLANKET
- ☐ SILT FENCE
- ☐ GEO-TEXTILE



# Landscape Fabric

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.teratuf.com](http://www.teratuf.com)



## Garden Weed Barrier



**PP non-woven weed barrier fabric** is an easy-to-use, environmentally safe fabric that controls weeds before they start.

### Frost Fleece

Material	100% Polypropylene, with or without uv
Width	600 mm ~2400mm (max 2.4m, or customized)
Length	50M, 100M, 200M, as per request
Weight	10gsm ~ 300gsm, as per request



## Plant Protection Fleece



This **garden fleece** is suitable to protect plants from frost. Good quality plant protection fleece in covering all crops vegetables seedlings, bedding plants, plants in pots from frost for the winter months. 10-30gsm gram weight can be placed directly over established plants veggies shrubs with no frame required.

### Product Specification

Material:	100% Virgin Polypropylene
Width:	600 mm ~2400mm (max 2.4m
Weight:	10gsm ~ 180gsm, as per request
Technics:	Spun-Bonded

### Product Features


- Earlier and increased harvest
- Protect against frost, snow, rain, heat, creeps, pest, birds
- Increase the growing temperature and extend the season

For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)





- ☒ **WOVEN FABRIC**
- ☐ **NON-WOVEN WEEDMAT**
- ☐ **NON-WOVEN BLANKET**
- ☐ **SILT FENCE**
- ☐ **GEO-TEXTILE**



# Woven Bags

QINGDAO TAIMEI PRODUCTS CO., LTD  
[www.taimeichina.com](http://www.taimeichina.com)



## PP Woven Sacks



### Application

- Chemicals, Fertilizers, Cement, Urea, Minerals
- Flour, Grain, Seeds, Spices, Pulses, Dates
- Sugar, Salt
- Sand, Metal Parts, Concrete Elements

**Woven PP Bags** are widely used for packing and transporting bulk commodities such as grains, salt, sugar and many more. They are also known for their durability, flexibility and low cost.

### PP Woven Bag

Raw Material	100% new virgin PP granule
Color	all colors available
Weave	commonly 9X9, 10X10, 11X11, 12X12, 14X14
Denier	700D to 1500D
Weight	65gsm to 220gsm
Composition	100% circular PP woven fabric
Size	300mm to 800mm Width, Length can be as requirement
Top	cut or hemmed
Bottom	Single folded, double folded, single stitch, double stitches
Printing	Up to 4 colors
Packaging	commonly bundles/bales/pallets

### Features

- Very affordable, lower cost
- Flexible and high strength, persistent durability
- Can be printed on both sides
- Water and dust proof design due to inside PE liners or laminated on the outside; hence, packed materials are protected from outside humidity
- Twisted weave and anti-skid print to prevent slipping
- Fully recyclable

For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)





- ☐ AGRICULTURE NET
- ☐ SUN SHADE SAIL
- ☐ SCREEN FENCE
- ☒ GREENHOUSE FILM



# Plastic Film

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.goldenthread.com](http://www.goldenthread.com)



## TUNNEL HOUSE FILM



## Greenhouse Film

Our greenhouse film is made using a five layer coextrusion process which allows for a wide range of added functionalities. Furthermore, the films improved mechanical resistance makes it suitable for greenhouse covers, macro and micro tunnels.

- Diffusion.
- Thermicity.
- Transmission.
- Anti-Dust.
- UV Block / Anti-virus.
- Anti-Drip.



### Greenhouse Poly Film

Description	5-layer, long life, colorless
Resins	EVA / LDPE / LLDPE / MLLDPE
Life Time(Kly)	350-550
Nominal Thickness	150-200
Average Thickness Tolerance	±5% on nominal thickness
Thickness Tolerance at any Point	±15%

### CUSTOM

\*Greenhouse cover can be cut to custom sizes.  
Please call for special customization options

For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)







A division of TAIMEI Group

- ☐ NON-WOVEN FABRIC
- ☒ WOVEN GEOTEXTILE
- ☐ GEOMEMBRANCE
- ☐ HDPE MEMBRANE
- ☐ GEOCELL



# Woven Geotextile

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.teratuf.com](http://www.teratuf.com)



# WOVEN GEOTEXTILE




## Woven Geotextile

are manufactured with high tensile strength and low elongation to provide dimensional stability and deliver superior load distribution, reducing rutting and extending the life of paved and unpaved roadways. This family of woven products offers proven performance, is compliant with AASHTO/NTPEP standards, and is available in a variety of styles to fit your specific project needs and specifications.



**Polypropylene Woven Geotextile**  
High tensile strength Synthetic Fabric



## Product Features

- High tensile strength
- UV Resistant
- Strong and Durable
- Resistant to Chemical Substances
- Resists biological degradation
- Resistant to ultraviolet degradation
- Strengthens and supports aggregates
- Increases performance life of the road
- Withstands tough construction loading
- Ease of installation

## Geotextiles Wovens

Property	Test Method	Unit	Light	Middle	Heavy
Weight	ASTM D5261	g/m <sup>2</sup>	130	170	215
Grab Tensile Strength	ASTM D4632	N	880	1100	1400
Grab Elongation	ASTM D4632	%	15	15	15
Tear Resistance	ASTM D4533	N	330	400	520
Puncture CBR	ASTM D4833	N	400	440	530
Permittivity	ASTM D4491	sec <sup>-1</sup>	0.05	0.05	0.05
Water Flow	ASTM D4491	L/min/m <sup>2</sup>	200	200	160
Apparent Opening Size	ASTM D4751	mm	0.3	0.42	0.42
U.V. Resistance	ASTM D4355	%@500h	70	70	70

Note: All information in this material is given in good faith but without warranty, expressed or implied with respect to the quality of fitness of the products referred to herein for any particular purpose.

For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)



QINGDAO TAIMEI PRODUCTS CO.,LTD.

Add.: No.6, Cuiling, Rd, Qingdao, China

Tel.: +86-532-88915029 / 88915092 website: [www.taimeichina.com](http://www.taimeichina.com)

Visit our website







A division of TAIMEI Group

- ☒ GEOMEMBRANE
- ☐ WOVEN GEOTEXTILE
- ☐ NON-WOVEN FABRIC
- ☐ GEOCELL
- ☐ HDPE MEMBRANE



# GEOMEMBRANE

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.teratuf.com](http://www.teratuf.com)






## Geomembrane (Dam Liner)

HDPE Geomembrane is manufactured from High Density Polyethylene resins. The surfaces of both sides are smooth. Used for a variety of environmental protection, agriculture and aquaculture waterproof and anti leakage.

SPECIFICATIONS												
Test		Unit	Standard									Test Frequency
Mechanical Properties	Thickness	mm	D5199	0.75	1.00	1.25	1.50	1.80	2.00	2.50	3.00	Per roll
	Density	g/cc	D1505/D792	0.94								90,000 kg
	Tensile Properties		D 6693									
	· yield strength	kN/m	Type IV	11	15	18	22	26	29	37	44	9,000 kg
	· break strength	kN/m		20	27	33	40	47	53	67	80	
	· yield elongation	%		12	12	12	12	12	12	12	12	
	· break elongation	%		700	700	700	700	700	700	700	700	
	Tear Resistance	N	D 1004	93	125	156	187	220	249	311	374	20,000 kg
	Puncture Resistance	N	D 4833	240	320	400	480	565	640	800	960	20,000 kg
	Stress Crack Resistance	hr.	D 5397	500 hr.								per GRI GM-10
Reference Properties	Carbon Black Content	%	D 4218	2.0-3.0%								9,000 kg
	Carbon Black Dispersion		D 5596	For 10 different views: 9 in Categories 1 or 2 and 1 in Category 3								20,000 kg
	Oxidative Induction Time (a) Standard OIT	min	D 3895	100 min.								90,000 kg
	(b) High Pressure OIT		D 5885	400 min.								
	Oven Aging at 85°C retained after 90 days	%	D 5721	55%								per each
	(a) Standard OIT - %		D 3895	80%								formulation
Roll size	UV Resistance											per each
	High Pressure OIT - % retained after 1600 hrs	%	D 5885	50%								formulation
Roll size	Dimensional Stability	%		±2								
	width	m		7	7	7	7		7	7	7	
	Length	m		280	210	168	140		105	84	70	
	Roll Area	m <sup>2</sup>		1960	1470	1176	980		735	588	490	



### CUSTOM

\*We can customize any size or order. Please call for special customization options

Visit our website



For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)





A division of TAIMEI Group

- ☒ NON-WOVEN FABRIC
- ☐ WOVEN GEOTEXTILE
- ☐ GEOMEMBRANE
- ☐ GEOCELL
- ☐ HDPE MEMBRANE



# NON-WOVEN GEOTEXTILE

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.teratuf.com](http://www.teratuf.com)




# Non Woven GEOTEXTILE



## NONWOVEN GEOTEXTILES

Made of polypropylene fibers, which provide excellent physical and hydraulic properties and are chemically stable in a wide range of environments. Primarily used for subsurface drainage, soil separation, filtration and rockslope protection. The high permeability properties provide high water flow rates for excellent filtration properties.



## SHORT FABRIC



Specifications													
Test	Units	BTS10	BTS15	BTS20	BTS25	BTS30	BTS35	BTS40	BTS45	BTS50	BTS60	BTS80	BTS120
Weight	g/m <sup>2</sup>	100	150	200	250	300	350	400	450	500	600	800	1200
Weight Variation	%	-8	-8	-8	-8	-7	-7	-7	-7	-6	-6	-6	-6
Thickness	mm	0.9	1.3	1.7	2.1	2.4	2.7	3	3.3	3.6	4.1	5	6.9
Width Variation	%	-0.5											
Break Strength (MD and XMD)	kN/m	2.5	4.5	6.5	8	9.5	11	12.5	14	16	19	25	38
Break Elongation	%	25 - 100											
CBR Burst Strength $\geq$	kN	0.3	0.6	0.9	1.2	1.5	1.8	2.1	2.4	2.7	3.2	4	6.2
Tear Strength (MD and XMD)	kN	0.08	0.12	0.16	0.2	0.24	0.28	0.33	0.38	0.42	0.46	0.6	0.82
MD=Machine Direction Strength CD=Cross Machine Direction Strength													
Sieve Size O90	mm	0.07 - 0.20											
Coefficient of Permeability	cm/s	(1.0-9.9) × (10 <sup>-1</sup> - 10 <sup>-3</sup> )											

## LONG FABRIC



Specifications of Long Fabric											
Specifications	Test Method	Unit	BTF100	BTF150	BTF200	BTF250	BTF300	BTF350	BTF400	BTF450	BTF500
Index Properties											
Ultimate Tensile Strength, MD	ASTM D4595	kN/m	7	11	14	17	19	24	27	30	37
Ultimate Tensile Strength, TD	ASTM D4595	kN/m	6	10	12	15	17	21	25	28	34
Tensile Elongation	ASTM D4595	%	45	45	50	50	50	60	60	60	60
Grab Tensile Strength, MD	ASTM D4632	N	400	600	850	1000	1250	1450	1700	1900	2100
Grab Tensile Strength, TD	ASTM D4632	N	350	550	700	900	1100	1250	1450	1600	1800
Grab Elongation	ASTM D4632	%	45	45	50	50	50	60	60	60	60
Trapezoid Tear Strength, MD	ASTM D4533	N	160	300	350	430	490	540	630	710	770
Trapezoid Tear Strength, TD	ASTM D4533	N	140	270	330	400	450	510	610	690	750
CBR Puncture Strength	ASTM D6241	N	1000	1800	2300	2700	3200	3600	4400	4800	5800
Apparent Opening Size O <sub>90</sub>	ASTM D4751	mm	0.12	0.11	0.11	0.10	0.09	0.09	0.08	0.08	0.08
Water Flow Q <sub>100</sub>	ASTM D4491	L/m <sup>2</sup> /s	250	235	220	200	185	165	125	110	90
Weight	ASTM D5261	g/m <sup>2</sup>	100	150	200	250	300	350	400	450	500
Thickness	ASTM D5199	mm	1.2	1.8	2.3	2.9	3.2	3.6	3.9	4.2	4.4
Roll Width	-	m	6	6	6	6	6	6	6	6	6
Roll Length	-	m	300	200	150	100	100	100	80	80	50



For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)



QINGDAO TAIMEI PRODUCTS CO., LTD.

Add.: No.6, Cuiling, Rd, Qingdao, China

Tel.: +86-532-88915029 / 88915092

website: [www.taimeichina.com](http://www.taimeichina.com)







A division of TAIMEI Group

- ☒ GEOCELL
- ☐ WOVEN GEOTEXTILE
- ☐ NON-WOVEN FABRIC
- ☐ GEOMEMBRANCE
- ☐ HDPE MEMBRANE



# Geocell

QINGDAO TAIMEI PRODUCTS CO., LTD

[www.taimeichina.com](http://www.taimeichina.com)    [www.teratuf.com](http://www.teratuf.com)



## Cellular confinement systems

also known as geocells—are widely used in construction for erosion control, soil stabilization on flat ground and steep slopes, channel protection, and structural reinforcement for load support and earth retention. This cellular confinement systems made with ultrasonically welded high-density polyethylene (HDPE) strips or novel polymeric alloy (NPA)—and expanded on-site to form a honeycomb-like structure—and filled with sand, soil, rock, gravel or concrete.



## Technical Spec (GB/T19274-2003)

Item Model	Open Width (cm)	Open Length (cm)	Cell Height	Welding Distance (mm)	Thickness (mm)	Weight (g)	Peeling Strenath (N/mm)	Welding Strenath (N/mm)	Yield strenath (N/mpa)
50-400	600	400	50	400	1	550	10	10	18
75-400	600	400	75	400	1	850	10	10	18
100-400	600	400	100	400	1	1100	10	10	18
150-400	600	400	150	400	1	1600	10	10	18
200-400	600	400	200	400	1	2200	10	10	18

Note: Beside 400 welding distance, we also have 150mm, 200mm, 300mm distance

For further information, please contact: [info@taimeichina.com](mailto:info@taimeichina.com)





- 
- Vinyl Tarps • Industrial Fabric • Shade & Tent Fabric
  - Sport Protection • Pitch cover • Pool cover
  - Plastic Film • Greenhouse film • Release Film
  - Landscape Weed Control Fabric
  - Plastic Net • Sun Shade Sail • PE Tarpaulin

Distributed By:



No.6, Cuiling Rd, Qingdao, China

Tel: +86-532-88915029 E-mail: [sales@taimeichina.com](mailto:sales@taimeichina.com)

[www.taimeichina.com](http://www.taimeichina.com)