



Optional Device 选购装置

- * Gusset Bag 插脚袋装置
- * Punch Hole 冲孔装置
- * Chain Bag 连包装置
- * Nitrogen Flushing 充氮气装置
- * Tear Notch 易撕口袋装置
- * Bag Support 上下托袋装置
- * Static Eliminator 除静电装置
- * PE Sealing System PE封口系统



Available for different weighing machine 适合各类称量装置

M Series Multihead Weigher
模块化多头组合秤



Auger Filler
高精高速管料计量



Volumetric Cup
量杯计量



Specification 规格:

| Model 型号 | SW-P420 | SW-P520 | SW-P620 | SW-Q500 |
|----------------------|---|-------------------|-------------------|---------------------|
| Bag length 制袋长度 | 60-300 mm(L) | 80-350 mm(L) | 80-400 mm(L) | 100-350mm |
| Bag width 制袋宽度 | 60-200 mm(W) | 80-250 mm(W) | 100-300 mm(W) | (70-180)/(40-100)mm |
| Max. film width 薄膜宽度 | 420 mm | 520 mm | 620 mm | 500 mm |
| Speed 速度 | 5-55 bags/min | 10-55 bags/min | 5-50 bags/min | 5-30bags/min |
| Film Thickness 膜厚度 | 0.04-0.09mm | 0.04-0.09mm | 0.04-0.09mm | 0.04-0.09mm |
| Air consumption 耗气量 | 0.65MPa | 0.65MPa | 0.8MPa | 0.8MPa |
| Voltage 电压 | 220V/50-60Hz | 220V/50-60Hz | 220V/50-60Hz | 220V/50-60Hz |
| Power 功率 | 2.2kW | 2.5kW | 4.0kW | 2.5kW |
| Machine Size 外型尺寸mm | 1080L*1300W*1400H | 1500L*1140W*1540H | 1250L*1600W*1700H | 1500L*1140W*1540H |
| Net Weight 机器重量 | 500kg | 600 kg | 800kg | 600kg |
| Option 选配 | Double servo motor available for higher speed up to 70bpm around 选配双伺服模式可提高速度到70包/分钟 | | | |

▲ The actual performance is subject to the exact project feature.

Advantages:

- * SIEMENS PLC control system, more stable and accuracy output signal, bag-making, measuring, filling, printing, cutting, finished in one operation;
- * Separate circuit boxes for pneumatic and power control. Low noise, and more stable;
- * Film-pulling with servo motor for precision, pulling belt with cover to protect moisture;
- * Open door alarm and stop machine running in any condition for safety regulation;
- * Film centering automatically is available (Optional);
- * Only control touch screen to adjust bag deviation. Simple operation;
- * Film in roller can be locked and unlocked by air, convenient while change film.

优势:

- * 采用西门子彩色触摸屏和稳定可靠的欧姆龙高精度输出的PLC控制、制袋、计量、充填、封合、打码、切袋一次性完成；
- * 气路控制和电路控制电箱独立分离，噪音小，电路更稳定；
- * 采用双皮带伺服拉膜：拉膜阻力小，包装袋成型好，更美观，皮带不易磨损。固定式放膜机构。安装包装膜更简单、更省时；
- * 包装袋的偏差调整只需在触摸屏上调整即可，操作简单；
- * 整机采用封闭式机构，有效防止粉尘进入机器内部；
- * 不锈钢和碳钢机型可选，满足多种需求。