

AT-4K1

- Special compound producing good cutting, wear resistances, long lift service.
- Wide and thick tread design providing good ground contact, traction and self-cleaning.



SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg) 10km/h	INFLATION PRESSURE (Kpa) 10km/h
					SW	OD		
5.00-8	8	3.00D	TT	14	132	465	1000	790
18X7-8	14	4.33R	TT	13	160	470	1220	900
6.00/6.90-9	10	4.00E	TT	17	160	545	1505	860
6.50-10	10	5.00F	TT	16	180	598	1655	790
7.00-12	14	5.00S	TT	18	190	682	2965	1000
8.25-12	12	5.00S	TT	16.8	210	728	2000	700
28X9-15/8.15-15	14	7	TT	18	221	706	3050	970
7.00-15/29x8-15	14	5.5	TT	17	200	732	3400	1000
8.25-15	16	6.5	TT	18.5	236	848	4610	930
32X14.5-15	24	11.5	TL	27	355	838	4945	1030
250-15	18	7.5	TT	20.5	250	735	4110	1030
300-15	20	8	TT	21	300	840	5940	930
7.50-16	16	6.00G	TT	17	213	820	5440	1030
9.00-20	16	7	TT	22.7	259	1018	5530	835
10.00-20	18	7.5	TT	40	300	1097	7255	1000
12.00-20	24	8.5	TT	45	320	1143	9800	1000
14.00-24	28	10	TT	40	375	1370	13500	1000
14.00-25	28	10.00/1.5	TT	40	375	1370	13500	1000

AT-4K2

- Special compound could be used in much more hard working sites.
- Non-symmetric tread offers more traction power and better wear-ability.
- Wide and extra deep tread provides stronger traction, longer life and puncture resistance.



SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg) 10km/h	INFLATION PRESSURE (Kpa) 10km/h
					SW	OD		
8.25-20RG	18	6.5	TT	32	235	975	5300	950
7.50-16RG	16	6.00G	TT	28	215	805	5400	1030
300-15RG	22	8	TT	29.5	295	840	7155	1030
250-15RG	20	7.5	TT	28.5	245	740	4580	1030
8.25-15RG	16	6.5	TT	32	242	870	4610	930
28X9-15/8.15-15RG	16	7	TT	27.5	221	706	3115	1000
28X9-15/8.15-15RG	24	7	TT	27.5	221	706	5670	1200
7.00-12RG	14	5.00S	TT	32.5	192	683	2965	1000
6.50-10RG	12	5.00F	TT	31.5	178	597	1860	970
6.00/6.90-9RG	12	4.00E	TT	26	168	555	1675	1030
5.00-8RG	10	3.00D	TT	23	142	468	1150	1000

AT-4K3

- Rugged Industrial Pneumatic tire Designed for Forklift Trucks, Terminal Tractors and Other Industrial Equipment Used in Heavy-Duty Applications.
- Special compound producing good cutting, wear resistances, long lift service.
- Wide and thick tread design providing good ground contact, traction.



SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg) 10km/h	INFLATION PRESSURE (Kpa) 10km/h
					SW	OD		
355/65-15	28	9.75	TT/TL	23	1000	6000	330	841