

CONTIRUN

DURUN

SIZE	RIM	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	LOAD CAPACITY(KG)						OTHER FORKLIFT
				BALANCE FORKLIFT						
				10KM/H		16KM/H		26KM/H		
DRIVE	STEER	DRIVE	STEER	DRIVE	STEER	DRIVE	STEER	16KM/H		
4.00-8	3.00/3.75	410/423	115/120	910	700	830	640	765	590	590
5.00-8	3.00/3.50/3.75	466	127	1255	965	1145	880	1060	815	815
15x4½-8	3	383	107	1005	775	915	705	850	655	655
16x6-8	4.33	416	156	1545	1190	1410	1085	1305	1005	1005
18x7-8 (180/70-8)	4.33	452	155	2430	1870	2215	1705	2060	1585	1585
6.00-9	4	533	140	1975	1520	1805	1390	1675	1290	1290
7.00-9	5	550	164	2670	2055	2440	1875	2260	1740	1740
18x7-9	4.33	452	155	2230	1780	2150	1615	2005	1505	1540
21x8-9	6	523	180	2890	2225	2645	2035	2455	1890	1890
6.50-10	5	582	157	2715	2090	2485	1910	2310	1775	1775
23x9-10	6.5	595	212	3730	2870	3405	2620	3160	2430	2430
200/50-10	6.5	458	198	2910	2240	2665	2050	2470	1900	1900
7.00-12	5	663	163	3105	2390	2835	2180	2635	2025	2025
8.25-12	5	732	202	3425	2635	3125	2405	2905	2235	2235
315/45-12(23X12-12)	10	679	244	3540	2735	3225	2505	3005	2335	2335
23x10-12	8	592	230	4450	3425	4060	3125	3770	2900	2900
27x10-12	8	680	236	4595	3535	4200	3230	3900	3000	3000
5.50-15	4.5	666	144	2525	1870	2415	1790	2195	1625	1495
6.00-15	4.5	694	148	2830	2095	2705	2000	2455	1820	1675
7.00-15	5.50/6.00	738	178	3700	2845	3375	2595	3135	2410	2410
7.50-15	5.5	768	188	3805	2925	3470	2670	3225	2480	2480
355/65-15	9.75	825	302	7800	5800	7080	5310	6000	4800	5450
8.25-15	6.5	829	202	5085	3910	4640	3570	4310	3315	3315
28*9-15 (8.15-15) (225/70-15)	7	700	230	4060	3125	3710	2855	3445	2650	2650
250-15	7.00/7.50	726	235	5595	4305	5110	3930	4745	3650	3650
300-15	8	827	256	6895	5305	6300	4845	5850	4500	4500
7.50-16	6	805	180	4400	3385	4025	3095	3730	2870	2870
9.00-16	6.00/6.50/7.00	880	212	5290	4070	4830	3715	4485	3450	3450
8.25-20	6.50/7.00	976	217	5335	4445	4870	4060	4525	3770	3770
355/50-20	10	831	312	15125	13605	14335	12945	8990	6915	14595
9.00-20	7.00/7.50	1005	236	6365	5305	5815	4845	5400	4500	4500
10.00-20	6.00/7.00/8.50/8.00	1041	248	7075	5895	6460	5385	6000	5000	5000
11.00-20	7.50/8.00	1058	270	7715	6430	7045	5870	6540	5450	5450
12.00-20	8.00/8.50	1112	285	8920	7435	8140	6785	7560	6300	6300
12.00-24	8.5	1218	300	9125	7605	8335	6945	7740	6450	6450
14.00-24	10	1340	328	12165	10135	11105	9255	10315	8595	8595

SIZE	RIM	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	LOAD CAPACITY(KG)						OTHER FORKLIFT
				BALANCE FORKLIFT						
				10KM/H		16KM/H		26KM/H		
DRIVE	STEER	DRIVE	STEER	DRIVE	STEER	DRIVE	STEER	16KM/H		
15x4.5-8	3	376	110	905	725	675	655	805	605	625
5.00-8	3	457	125	1210	970	1175	880	1095	820	840
16x6-8	4.33	412	152	1500	1200	1445	1085	1345	1010	1035
18x7-8	4.33	457	160	2350	1880	2265	1700	2110	1585	1620
6.00-9	4	528	148	1920	1535	1855	1390	1730	1295	1325
21x8-9	6	518	194	2810	2250	2715	2035	2530	1895	1940
6.50-10	5	572	168	2840	2110	2545	1910	2370	1780	1820
23x9-10	6.5	577	208	4005	3205	3845	2885	3605	2705	2765
200/50-10	6.5	455	196	2370	1900	2290	1720	2135	1605	1630
7.00-12	5	654	178	3015	2410	2910	2185	2710	2035	2075
23x10-12	8	590	230	3980	3420	3820	3210	3586	3010	2980
7.00-15	5.5	714	190	3590	2870	3465	2600	3225	2420	2475
28x9-15	7	691	219	4090	3270	3945	2960	3675	3755	2820
8.25-15	6.5	818	210	4940	3950	4765	3575	4440	3330	3045
250-15	7.5	724	234	4366	3400	4220	3160	3930	2955	3010
300-15	8	819	264	5990	4700	5780	4335	5380	4037	4130
12.00-20	8.0/8.5	1090	283	8800	7000	8500	6925	8000	6450	6595



SIZE OF TIRE	RIM SIZE	PATTERN	OD	SW	Max Load(Kg)
			±5mm	±5mm	Other Industrial vehicles(16km/h)
2.00-8(12x4)	2.50/3.00	AP-SM	318/310	103/100	380
2.00-8(12x4)	2.50/3.00	AP-RIB	318/310	103/100	380
2.00-8(12x4)	2.50/3.00	SC-LUG2	318/310	103/100	380
3.00-5	2.15	SC-LUG4	268/250	77/72	330
3.00-5	2.15	AP-LUG4	268/250	77/72	330
3.20-8	3	AP-RIB	328	110	520
3.50-5	3	CONTIRUN	300	100	380
3.60-8	3	AP-RIB	368	110	600
4.00-4	2.50C	CONTIRUN	300	100	380
4.00-8(Wide)	3.75	AP-RIB	423	120	730
4.00-8	3.00/3.75	CONTIRUN	410	115	695
4.00-8	3.00/3.75	AP-RIB	410	115	695
16x5-9	3.50/4.00	AP-RIB	404	126	710
300x125	Molded-On	AP-SM	302	125	910
350x100	Molded-On	AP-SM	352	100	850
6.50-10	5	APLUG3	566	153	1820
5.50-15	4.5	APLUG2	666	144	1495
8.25-16	9.75	APLUG1	706	300	3955
4.00-8	3.00/3.75	AP-RIB	410/423	115/120	590
10.00-20	7.50/8.00	AP-SM	1041	248	5000