



# AP-SKS



# AP-TG



## Application

- ▶ Front Loader
- ▶ Auger
- ▶ Snow Plow
- ▶ Hammer
- ▶ Articulating Booms
- ▶ Telescopic Booms
- ▶ Telehandlers
- ▶ Trencher

## Features

- ▶ Superhigh load capacity
- ▶ High Stability and Safty
- ▶ Special Sidewall design gives excellent cushion fuction and driving comfort
- ▶ Excellnt wear resistance, climbing, steering dexterity, start torque and tread grip
- ▶ The specially composed formulation provides a good anti-cutting performance, good puncture resistance

SIZE	RIM	O.D. (mm)	S.W. (mm)	CAPACITY(25km/h)	ALTERNATIVE TIRE MODEL	MACHINE MODEL
31x10-16	6.00-16	790	236	2945 kgs	31X6X10 10-16.5	Bobcat,Caterpillar
33x12-20	8.00-20	837	290	4045 kgs	33X6X11 12-16.5	Bobcat,Caterpillar
36x14-20	8.00-20	914	355	6115 kgs	14-17.5	Genie S60,JLG600S
38.5X14-20	11.00-20	966	350	6360 kgs	-	-
15.00-20	11.00-20	965	345	4200 kgs	-	Boom lift
18.00-20	12.00-20	1060	430	6800 kgs	-	Boom lift
385/65-24	10.00-24	1060	360	16800 lbs / 7636 kgs	15-22.5 385/65D22.5	Genie S-3200,S80,JLG-860
445/65-24	12.00-24	1150	430	19800 lbs / 9000 kgs	18-22.5 445/65D22.5	Genie S-3800,S-100, S-125,JLG1350

SIZE	RIM	O.D.(mm)	S.W.(mm)	CAPACITY(25km/h)	ALTERNATIVE TIRE MODEL	MACHINE MODEL
13.00-24	8.5	1290	315	9265 kgs	-	JLG
14.00-24	8.50/10.00	1336	350	10645 kgs	-	JLG