

PNSM / PNRN / PNTR



Application

- ▶ Battery Fork Lifts ▶ Trolleys ▶ Pallet Trucks ▶ Rotators
- ▶ Trailers ▶ Road Milling ▶ Stackers ▶ Different material handling equipments.

Features:

- ▶ The precision engineered steel band / rubber construction provides maximum reliability and productivity.
- ▶ Minimal deformation of the tyre while carrying loads ensures better truck- and load stability.
- ▶ The large load carrying capability of press-on tyres makes them suitable for today's most demanding applications.
- ▶ Available in Traction (treaded), LUG and Smooth pattern. Available in Non-Marking compound also.

TYRE SIZE		LOAD CAPACITY IN KG										
INCH	MM	COUNTER BALANCED LIFTING EQUIPMENTS						OTHER VEHICLES				
		10 KM/H		16 KM/H		20 KM/H		6 KM/H	10 KM/H	16 KM/H	20 KM/H	TRAILER
		LOAD WHEELS	STEER WHEELS	LOAD WHEELS	STEER WHEELS	LOAD WHEELS	STEER WHEELS					
8 1/2x4x4	216-102-101.6	700	575	625	525	525	415	750	550	500	375	750
9x5x5	229-127-127.0	960	790	855	720	720	570	1030	755	685	515	1030
10 1/2x5x6 1/2	267-127-165.1	1075	885	960	810	810	640	1155	845	770	575	1155
10 1/2 x6x6 1/2	267-152-165.1	1335	1095	1190	1000	1000	795	1430	1050	955	715	1430
10 1/2 x7x6 1/2	267-178-165.1	1600	1315	1430	1200	1165	955	1715	1260	1145	860	1715
10x4x6 1/2	254-127-165.1	780	640	695	585	585	465	835	610	555	415	835
10x4x6 1/4	254-102-158.8	785	615	700	590	590	465	840	615	560	420	840
10x5x6 1/2	254-127-165.1	1015	835	905	760	760	605	1085	795	725	545	1085
10x5x6 1/4	254-127-158.8	1025	845	915	770	770	610	1100	805	735	550	1100
10x6x6 1/4	254-152-158.8	1265	1040	1130	950	950	755	1360	995	905	680	1360
12x4 1/2x8	305-114-203.2	1040	855	930	780	780	620	1115	820	745	560	1115
12x4x8	305-102-203.2	905	745	810	680	680	540	970	710	645	485	970
12x5 1/2x8	305-140-203.2	1340	1100	1195	1005	1005	795	1435	1050	955	715	1435
12x5x8	305-127-203.2	1190	975	1060	890	890	710	1275	935	850	635	1275
12x6 1/2x8	305-165-203.2	1620	1330	1450	1215	1215	965	1740	1275	1160	870	1740
13 1/2x4 1/2x8	343-114-203.2	1145	940	1020	860	860	680	1225	900	820	615	1225
13 1/2x5 1/2x8	343-140-203.2	1510	1240	1350	1135	1135	900	1620	1185	1080	810	1620
13x3 1/2x8	330-89-203.2	870	715	775	645	645	620	1030	680	60	470	1030
13x4 1/2x8	330-114-203.2	1115	920	995	840	840	665	1195	880	800	600	1195
13x5x8	330-127-203.2	1290	1060	1150	965	965	765	1380	1010	920	690	1380
14x4 1/2x8	356-114-203.2	1165	955	1040	875	875	695	1250	915	830	625	1250
14x5x10	356-127-254.0	1335	1100	1195	1000	1000	795	1430	1050	955	715	1430
15 1/2x5x10	394-127-254.0	1475	1210	1315	1105	875	1580	1580	1155	1050	790	1580
15 1/2x6x10	394-152-254.0	1865	1530	1665	1395	1395	1110	1995	1465	1330	1000	1995
15x4x11 1/4	381-102-285.8	1065	875	950	800	775	635	1140	835	760	570	1140
15x5x11 1/4	381-127-285.8	1390	1145	1240	1045	1045	830	1490	1095	995	745	1490
15x6x11 1/4	381-152-285.8	1720	1410	1535	1290	1290	1025	1840	1350	1225	920	1840
16 1/4x5x11 1/4	413-127-285.8	1525	1250	1360	1145	1145	905	1635	1200	1090	815	1635
16 1/4x6x11 1/4	413-152-285.8	1915	1570	1710	1435	1435	1140	2050	1505	1365	1025	2050
16 1/4x7x11 1/4	413-178-285.8	2320	1905	2070	1740	1740	1380	2485	1820	1655	1245	2485
16 1/4x8x11 1/4	413-203-285.8	2710	2225	2420	2030	2030	1615	2905	2130	1935	1450	2905