



AP-SKS



AP-TORKY

AP-LMAX

AP-TOPEX



Application

- ▶ Grader
- ▶ Mobile crane
- ▶ Front loader
- ▶ Wheel loader
- ▶ Backhoe loader
- ▶ Dumper

Features

- ▶ Special designed tread pattern for toughest application.
- ▶ Excellent tread compound formula provide the extraordinary chunking and cutting resistance properties.
- ▶ Unique aperture sidewall design ensure the best riding confort.

TYRE SIZE	STANDARDS RIM	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	MAX LOAD (KG)		
				10MPH	16MPH	25MPH
8.25-16	6.5	805.0	194.0	4940.0	4765.0	4440.0
9.00-16	6.0	890	220	5841	5310	4500
10.00-16	6.0	890	220	5841	5310	4500
20.5/70-16	10.0	878	275	6135	5965	5625
16/70-16	10.0	878	275	6135	5965	5625
16/70-20	13.0	1012	375	9445	9105	8600
9.00-20	6.50	952	210	6450	6235	5805
10.00-20	8.00	1036	256	7240	6995	6510
11.00-20	8.00	1058	268	7560	7300	6810
12.00-20	8.50	1113	243	8445	8105	7600
14.00-24	10.00	1295	308	11865	11390	10680

TYRE SIZE	STANDARDS RIM	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	MAX LOAD (KG)						OTHER INDUSTRIAL VEHICLES
				10MPH		16MPH		25MPH		
				DRIVING	STEERING	DRIVING	STEERING	DRIVING	STEERING	

AP-TORKY

16.00-25	11.25	1446	390	16860	13490	15170	11400	13480	10130	10130
18.00-25	13.00	1620	500	21200	16960	20480	15400	19100	14360	14360
14.00-20	10.00	1220	321	10800	8640	10430	7840	9730	7315	7450
14.00-24	10.00	1348	323	12165	10135	11105	9255	10315	8589	8800
17.5-25	14.00-25	1344	437	17720	14180	16880	12690	15960	12000	12000
20.5-25	17.00-25	1490	530	24430	18820	22290	17170	20660	15880	15880
23.5-25	19.00-25	1585	585	30830	24660	29790	22400	27770	20880	20880
26.5-25	22.00-25	1750	670	39300	31400	37400	28100	35400	26600	26600

AP-LMAX

17.5-25	14.00	1368	458	17720	14180	16880	12690	15960	12000	12000
20.5-25	17.00	1455	500	24430	18820	22290	17170	20660	15880	15880
23.5-25	19.50	1620	580	30830	24660	29790	22400	27770	20880	20880
26.5-25	22.00	1715	642	39300	31400	37400	28100	35400	26600	26600
29.5-25	25.00	1840	730	48100	37055	43880	33800	40340	31265	31265

AP-TOPEX

17.5-25	14.00	1340	440	17720	14180	16880	12690	15960	12000	12000
20.5-25	17.00	1500	520	24430	18820	22290	17170	20660	15880	15880
23.5-25	19.50	1610	556	30830	24660	29790	22400	27770	20880	20880
26.5-25	22.00	1720	670	39300	31400	37400	28100	35400	26600	26600