



AP-SKS / CONTIRUN / AP-RIB



AP-TORKY / AP-LMAX / AP-UTY



SIZE	RIM	TIRE WITH HOLE (YES/NO)	PATTERN NO.	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD(KG)
				±5MM	±5MM	OTHER INDUSTRIAL VEHICLES (16KM/H)
10×16.5(30×10-16)	MOLDED-ON	Yes	AP-SKS	788	250	3700
12×16.5(33×12-20)	MOLDED-ON	Yes	AP-SKS	840	275	4500
16/70-20	MOLDED-ON	Yes	AP-SKS	1060	400	8830
16/70-20(III)	MOLDED-ON	Yes	AP-SKS	940	330	6620
38.5×14-20(14×17.5)	MOLDED-ON	Yes	AP-SKS	966	350	7070
385/65-24(385/65-22.5)	MOLDED-ON	Yes	AP-SKS	1062	356	7390
445/65-24(445/65-22.5)	MOLDED-ON	Yes	AP-SKS	1152	428	10040
12.00-20	MOLDED-ON	No	AP-RIB	1112	285	7645
14.00-24	MOLDED-ON	No	AP-RIB	1250	316	9496
14.00-24	MOLDED-ON	No	CONTIRUN	1340	328	10700
17.5-25	MOLDED-ON	Yes	AP-LMAX	1368	458	13400
18.00-25	MOLDED-ON	Yes	AP-TORKY	1620	500	15795
20.5-25	MOLDED-ON	No	AP-LMAX	1455	500	17470
23.5-25	MOLDED-ON	Yes	AP-LMAX	1620	580	23400
26.5-25	MOLDED-ON	Yes	AP-LMAX	1715	642	29260
29.5-25	MOLDED-ON	Yes	AP-LMAX	1840	730	34390

SIZE	PATTERN NO.	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD(KG)
		±1MM	±5MM	OTHER INDUSTRIAL VEHICLES (16KM/H)
8.25-20	CONTIRUN	976	217	4230
10.00-20	CONTIRUN	1041	248	5300
12.00-20	CONTIRUN	1112	285	7645
12.00-24	CONTIRUN	1218	300	7690
14.00-20	AP-RIB	1250	316	9495
14.00-24	CONTIRUN	1340	328	10700
16.00-25	AP-TORKY	1460	410	13340
17.5-25	AP-LMAX	1368	458	13400
20.5-25	AP-LMAX	1455	500	17660
18.00-33	AP-UTY	1840	450	18380
54×26	AP-UTY	1370	660	23130
55×18-34	AP-UTY	1410	450	15050
1510×470	AP-UTY	1516	470	16120
1098×500	AP-TORKY	1098	500	14235