



AT-COM

- Wide section for good flotation force and steering ability special for desert transportation and road compactor application.


SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg) 10km/h	INFLATION PRESSURE (Kpa) 10km/h
					SW	OD		
23.1-26	12	DW20	TT/TL	29	595	1500	200	5150
23.1-26	14	DW20	TT/TL	29	595	1500	230	5600
23.1-26	16	DW20	TT/TL	29	595	1500	260	6150



AT-RS

- Designed for roller tractor, higher stability, wider contact area and smooth profile for efficient compaction.
- Low rolling resistance for economy performance.

SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg) 10km/h	INFLATION PRESSURE (Kpa) 10km/h
					SW	OD		
7.50-15	6	6	TT	15	215	785	1850	400
7.50-15	14	6	TT	15	215	785	2850	825
8.5/90-15	6	6	TL	15	220	785	1700	345
9.00-20	16	7.00	TT	15	259	1018	4750	725
11.00-20	18	8.00	TT	16	293	1085	6000	825
13/80-20	16	11	TT	16	319	1061	5430	800
14/70-20	14	11	TT	16	325	1045	6000	900



AT-GSE1

- Produces and distributes a wide range of ground support equipment tires for the aerospace industry including lifts, baggage carts, tractors, passenger boarding bridges and more.
- Longer Tread Life and tougher Side-Walls to reduce downtime.


SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg) 10km/h	INFLATION PRESSURE (Kpa) 10km/h
					SW	OD		
28X8-15	14	6	TT	24	212	732	2245	975
185-14	10	5.50F	TL	20	184	635	1120	655
165-13	10	4.5	TL	21.5	177	608	1050	655



AT-GSE2

- Produces and distributes a wide range of ground support equipment tires for the aerospace industry including lifts, baggage carts, tractors, passenger boarding bridges and more.
- Longer Tread Life and tougher Side-Walls to reduce downtime.


SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg) 10km/h	INFLATION PRESSURE (Kpa) 10km/h
					SW	OD		
9.50-16.5	10	6.75	TL	18	241	780	1440	550
8.75-16.5	10	6.75	TL	19	225	772	1410	520
8.00-16.5	8	6	TL	14	203	726	1410	450
225/75D16	10	6	TL	19	224	750	1605	790
225/75-15	10	6	TL	19	224	750	1635	725
7.50-10	16	5.50F	TT	16	203	647	1580	1030
6.50-10	12	5.00F	TT	18	178	597	1150	970
6.90-9	10	4.00E	TT/TL	18	175	546	1280	860
6.90-9	8	4.00E	TL	13	175	546	1125	690
5.00/5.70-8	8	3.75	TL	12.5	146	480	665	830
4.00/4.80-8	8	3.75	TL	13	124	432	525	790



AT-GSE3

- Produces and distributes a wide range of ground support equipment tires for the aerospace industry including lifts, baggage carts, tractors, passenger boarding bridges and more.
- Longer Tread Life and tougher Side-Walls to reduce downtime.

SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg) 10km/h	INFLATION PRESSURE (Kpa) 10km/h
					SW	OD		
8.75-16.5	10	6.75	TL	19	225	772	1410	520
225/75D16	10	6	TL	19	224	750	1605	790



AT-GSE4

- Produces and distributes a wide range of ground support equipment tires for the aerospace industry including lifts, baggage carts, tractors, passenger boarding bridges and more.
- Longer Tread Life and tougher Side-Walls to reduce downtime.

SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg) 10km/h	INFLATION PRESSURE (Kpa) 10km/h
					SW	OD		
8.75-16.5	12	6.75	TL	25	225	772	1520	655
225/75D16	12	6	TL	25	224	784	1735	655

