

AT-UB3

- The carcass is strong enough for heavy loading application.
- Resistant for tread penetration Reinforced Sidewall Design.
- Preventing sidewall cutting Unique Chafer Design.
- Reinforced chafer design for heavy loading capacity.

SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg)	INFLATION PRESSURE (kPa)
					SW	OD		
14.00-20	28	10	TT	29	375	1245	9250	965
14.00-20	32	10	TT	29	375	1245	10025	--
50X20-20	36	15	TL	33	495	1270	12940	1030

AT-UB5

- The carcass is strong enough for heavy loading application.
- Resistant for tread penetration Reinforced Sidewall Design.
- Preventing sidewall cutting Unique Chafer Design.
- Reinforced chafer design for heavy loading capacity.

SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg)	INFLATION PRESSURE (kPa)
					SW	OD		
12.00-20	28	8.5	TT	61	320	1143	9910	1030

AT-UBL4

SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg)	INFLATION PRESSURE (kPa)
					SW	OD		
69X18.00-35	50	13.00/2.5	TL	52	455	1750	25000	1175
63X18.00-35	50	13.00/2.5	TL	50	445	1600	25000	1175
1425X585-27	52	20.5/2.5	TL	50	590	1430	35000	1200
17.5-25	20	14.00/1.5	TT/TL	50	445	1400	8250	575

AT-SV1

- Weight distributed across a huge footprint for less compaction and turf disturbance.
- Shallow tread depth and wide width for high flotation.

SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg)	INFLATION PRESSURE (Kpa)
					SW	OD		
66x44.00-25	20	36	TL	12	1118	1720	7020	345
66x44.00-25	24	36	TL	12	1118	1720	10000	345
66x44.00-25	26	36	TL	12	1118	1720	12000	345

AT-SV2

- Weight distributed across a huge footprint for less compaction and turf disturbance.
- More tread depth and wide width for high traction and flotation.

SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg)	INFLATION PRESSURE (Kpa)
					SW	OD		
66x43.00-25	12	36	TL	37	1050	1700	5700	290
66x43.00-25	16	36	TL	37	1050	1700	6100	290
66x43.00-25	20	36	TL	37	1050	1700	6600	310

AT-SAND / AT-SAND+

- E-7 special compound producing good resistance to the high temperature.
- Flat and wide foot print suitable for flotation applications on soft soil, orchards, etc.
- Tread specially designed to given minimum ground disturbance.
- Increased tread depth and strong carcass ensuring long life.

SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg)	INFLATION PRESSURE (Kpa)
					SW	OD		
9.00-16	8	6.50H	TT/TL	10	245	860	1320	310
9.00-17	8	7J	TT/TL	10	245	880	1320	310
14.00-20	18	10.00W	TT/TL	10	355	1207	4125	245
16.00-20	16	10.00W	TT/TL	14	419	1323	5450	245
20-20	14	17	TL	15	555	1075	4125	280
20-20	14	14.00T	TT/TL	15	505	1180	6000	360
18-20	14	14.00T	TT/TL	15	455	1080	4625	360
18.00-25	16	TL	TL	16	470	1557	7750	245

AT-MON

- Low ply rating and low tread depth design lightening tires.
- Super wide tread design and special construction improving the tire stability and casing strength.

SIZE	PR	RIM	TUBE TYPE	TREAD DEPTH (mm)	INFLATED DIMENSIONS (mm)		LOAD CAPACITY (kg)	INFLATION PRESSURE (Kpa)
					SW	OD		
66x43.00-25	6	36	TL	13	1050	1650	4500	170
66x43.00-25	8	36	TL	13	1050	1650	5000	210