


产品质量证明书

INSPECTION CERTIFICATE

订货单位: 太钢中部 (山西) 销售有限公司		产品名称: 不锈钢热轧钢带		标准 Specification		牌号 Grade		
Customer:		Product: Hot rolled stainless steel coil		GB/T713.7-2023, ASME SA-240M-2023		S30408/304		
收货单位: 太原太钢大明金属科技有限公司		供货状态: 1D/No.1 固溶 酸洗 不切边						
Purchaser:		Condition: 1D/No.1; Solution annealed; Pickling; M						
合同号 Mill'S No. J258T11702		客户订单 Customer Order No.		交货单号 Delivery Order No. GFT250801029		证书编号 Certificate No. 0045000909069731		车号 Train Wagon No. 晋AA2247

序号 No	材料号 Material No.	炉号 Heat No.	规格 Dimensions(mm)	数量 Quantit	重量 Weight (t)	分析 Max. Min.	C%	Si%	Mn%	P%	S%	Cr%	Ni%	N%
1	FA5081235	A0503156	8*1500	1	25.620	H	0.04	0.62	1.01	0.031	0.004	18.22	8.00	0.06
合计 Total				1	25.620	尺寸及外观 Acceptable Visual And Dimensions: 合格 OK								

序号 No.	位置 方向 P.D.	屈服强度 Y.S. Rp0.2 MPa 常温	屈服强度 Y.S. Rp1.0 MPa 常温	抗拉强度 T.S. Rm MPa 常温	伸长率 EL. A5 % 常温	伸长率 EL. A50 % 常温	硬度 Hardness HBW 常温	硬度 Hardness HBW 常温	晶间腐蚀 I G C
1	2 1	285	327	664	56.5	60	187	187	OK



注释 Notes	M=Not cutting edge; H=熔炼分析 Heat analysis; P=成品分析 Product analysis; D=电渣重熔分析 Electroslag remelting; Y.S.=Yield Strength; 常温 = Normal Temperature (Room Temperature); T.S.=Tensile Strength; EL.=Elongation; A5:Lo=5.65SQRT(So); A50:Lo=50mm; I G C=Intergranular corrosion; 2=横向 Transverse; 1=纵向 Longitudinal;	腐蚀方法 Corrosion Methods GB/T 4334 E
声明 Declare	 本产品仅限国内销售不得出口, 经销商向用户出具本质量证明书复印件需加盖其公章。 This product is for domestic sales in China only. Export is not allowed. This certificate, if provided by a re-seller in photocopy, is invalid unless with the re-seller's company stamp.	
备注 Remarks		


 ZHAO JINLEI
 质量负责人 Quality Manager