



RIYANG ATLA Series

Fitting Fabrication Machine

EN 2022

RIYANG ATLA Series Fitting Fabrication Machine



STANDARD COMPOSITION

- Basic machine complete with two carriages, both driven by hydraulic system.
- Manual hydraulic control panel with all functional keys and buttons plane layout.
- Electrical trimmer with gear and safety micro switch.
- PTFE coated heating plate with steel shield.
- Left and right elbow clamps ϕ 400mm with full set of aluminum inserts from ϕ 90mm to ϕ 355mm.
- Left and right 90° Tees and Crosses clamps ϕ 400mm with full set of aluminum inserts from ϕ 90mm to ϕ 355mm.

OPTIONAL ACCESSORIES

- 45° and 60° Wyes clamps ϕ 315mm with full set of aluminum inserts from ϕ 90mm to ϕ 280mm.
- Stub end device
- Narrow clamps and inserts
- Data logger

- Welding Range:  : 90 - 400mm  : 90 - 400mm  : 90 - 315mm

- Power Supply: 380 V, 50/60 Hz
- Rated Power: 12.3 kW
- Piston Area: 10.9 cm²
- Material: PE-PP-PPR-PVDF
- Net Weight: 1740 kg
- Dimension: 1630 x 1800 x 1350 mm