

# EAST E210 GROW ROOM DEHUMIDIFIER

## PERFORMANCE PARAMETERS

Water Removal @80°F, RH60%	210 Pints/Day
Water Removal @30°C, RH80%	150 Liters/Day (320 Pints/Day)
Efficiency(@80F/60%RH)	4.1 L/kW-hr (7.3 pints/kW-hr)

## TECHNICAL PARAMETERS

Supply Voltage	208~230V / 60Hz
Rated Power(@230V)	1.3 Kw
Rated Amps	5.5 A
Operating Temperature	41°F ~100°F
Air Volume @ 0.0" ,CFM	562 CFM
Static Pressure	50~80 Pa
Compressor Cooling Capacity	14,330 BTU
Refrigerant Type	R410a
Net Dimensions	27.4" x 21.3" x 18.5"
Net Weight	134 Lb
Throttling	Thermal Expansion Valve
3rd-party Port	Trolmaster HS-1 Port Ready

## 👍 FEATURES

- Engineered for high-performance grow room
- EDD System (EAST Directly Drive 0.02s start)
- Fast service maintaining
- Detachable Digital Control
- Sturdy Frame Structure replaces conventional flat panel structure
- Aluminum Alloy Non-woven Filter
- Third-party ready terminals

