



SIZE	L	D		K		G		n-φd		C
		PN10	PN16	PN10	PN16	PN10	PN16	PN10	PN16	
DN50	210	165	165	125	125	102	102	4-φ19	4-φ19	19
DN65	225	185	185	145	145	122	122	4-φ19	4-φ19	19
DN80	247	200	200	160	160	138	138	4-φ19	8-φ19	19
DN100	295	220	220	180	180	158	158	8-φ19	8-φ19	19
DN125	295	250	250	210	210	188	188	8-φ19	8-φ19	19
DN150	360	285	285	240	240	212	212	8-φ23	8-φ23	19
DN200	435	340	340	295	295	268	268	8-φ23	12-φ23	20
DN250	495	395	405	350	355	320	320	12-φ23	12-φ27	22
DN300	555	445	460	400	410	370	378	12-φ23	12-φ27	24.5

5	BOLT+WASHER	C. S/S. S	2	
4	RUBBER DISC	STEEL+NR	1	
3	BONNET	CI/DI	1	
2	GASKET	RUBBER	1	
1	BODY	CI/DI	1	
NO.	PARTS NAME	MATERIAL	QTY	
TEST PRESSURE		SHELL		SEAL
	HYDROSTATIC	2.4 MPa		1.76 MPa
	AIR			
STANDARD	DESIGN CODE			
	INSPECTION & TEST		API 598	
	END STANDARD		DIN PN10/PN16	
	FACE TO FACE			
TITLE : RUBBER DISC CHECK VALVE				
APPROVED	申广建			REV
CHECKED	程志峰			
DRAWN	李强		HEBEI HONBBANG VALVE CO.,LTD	
DESIGNED	王明	SCALE	UNIT	mm
SIGNATURE				