


- Technical Specifications**
1. Valve: Wafer Type PTFE-Lined Butterfly Valve;
 2. Valve Design: API 609
 3. Face to Face: API 609 Table A
 4. Inspection and Test: API 598
 5. Flange Drilling: CLASS 150, JIS 10K, PN10/16
 5. Top Flange: EN ISO 5211;
 7. W.T. Range(°C) : -20 ~ +150°C.
 6. LEVER OP.: DN50-150
GEAR OP.: DN200

8	Bearing	SS304+PTFE
7	Belleville Washer	SS304
6	Pusher	SS304
5	O-ring	FKM
4	Disc	CF8+PFA
3	Liner	PTFE
2	Stem	SS416
1	Body	WCB
No.	Part Name	Material

400	102	470	270	230	540	16-ø29	510	16-ø27	515	16-ø25	525	16-ø30	
350	78	420	400	325	476	12-ø29	445	16-ø25	460	16-ø23	470	16-ø26	
300	78	395	400	325	432	12-ø25	400	16-ø25	400	12-ø23	410	12-ø26	
250	68	344	300	225	362	12-ø25	355	12-ø25	350	12-ø23	355	12-ø26	
200	60	296	250	215	298.5	8-ø23	290	12-ø23	295	8-ø23	295	12-ø23	
DN	L	H	ø	W	øF	n-ød	øF	n-ød	øF	n-ød	øF	n-ød	
				ANSI 150		JIS 10K		PN10		PN16			
DRN				CHK				APP				SCALE	1 : 1



MATERIAL
UNIT mm

FULL LINED Butterfly Valve
DATE
REV