



STEEL PIPE SINCE 1991
BAOLAI

IMC Conduit Fittings

IMC Conduit 90° Elbow, HDG



Material	Steel
Finish	Hot dip galvanized
Standard	UL 1242 / ANSI C80.6
Thread	NPT
Size	1/2" to 4"
Usage	Used to connect IMC Conduit together to allow for 90 degree bends.

IMC Conduit 90° Elbow, PG



Material	Steel
Finish	Pre-galvanized
Standard	ANSI C80.6
Thread	NPT
Size	1/2" to 2"
Usage	Used to connect IMC Conduit together to allow for 90 degree bends.



Phone: +86 022 83377302

Email: info@baolaisteel.com

Rigid Conduit 90°
Elbow, HDG



Material	Steel
Finish	Hot Dip Galvanized
Standard	UL 6
Thread	NPT
Size	1/2" to 6"
Usage	installed on conduit raceways for the interconnection of conduit runs and other fittings.

Rigid Conduit 45°
Elbow, HDG



Material	Steel
Finish	Hot Dip Galvanized
Standard	UL
Thread	NPT
Size	1/2" to 6"
Usage	installed on conduit raceways for the interconnection of conduit runs and other fittings.

IMC Coupling, EG



Material	Steel
Finish	Galvanized
Standard	UL 1242
Thread	NPSL
Size	1/2" to 4"
Usage	Used to join two lengths of threaded Rigid or IMC conduit.

Rigid Coupling, EG



Material	Steel
Finish	Galvanized
Standard	UL 6 / ANSI C80.1
Thread	NPT
Size	1/2" to 6"
Usage	Used to join two lengths of threaded Rigid or IMC conduit.

Rigid Coupling, HDG



Material	Steel
Finish	Hot dip galvanized
Standard	UL 6 / ANSI C80.1
Thread	NPT
Size	1/2" to 6"
Usage	Used to join two lengths of threaded Rigid or IMC conduit.

Rigid Set Screw Connector



Material	Steel
Finish	Zinc Plated
Standard	UL 514B
Size	1/2" to 2"
Usage	Used to bond unthreaded Rigid or IMC conduits to electrical junction boxes or electrical enclosures.



Rigid Set Screw Coupling



Material	Steel
Finish	Galvanized
Standard	UL 6 / ANSI C80.1
Thread	NPT
Size	1/2" to 2"
Usage	Used to bond two length of unthreaded Rigid or IMC conduits.

Rigid Compression Connector



Material	Steel
Finish	Galvanized
Standard	UL 6 / ANSI C80.1
Thread	NPT
Size	1/2" to 2"
Usage	Used to join IMC / Rigid Conduit to knock-outs in concrete-tight box or damp location applications.

Rigid Compression Coupling



Material	Steel
Finish	Galvanized
Standard	UL 6 / ANSI C80.1
Thread	NPT
Size	1/2" to 2"
Usage	Used to join two length of IMC / Rigid Conduit.



Lloyd's Register



Phone: +86 022 83377302

Email: info@baolaisteel.com



Rigid Watertight Hub



Material	Zinc Die Cast
Finish	Galvanized
Standard	UL 514B
Thread	NPT
Size	1/2" to 4"
Usage	Connect rigid or IMC conduit to a load center or other metal enclosure where a weather-tight joint is required.

Grounding Watertight Hub



Material	Malleable Iron
Finish	Galvanized
Standard	UL 514B
Thread	NPT
Size	1/2" to 6"
Usage	Connect rigid or IMC conduit to a load center or other metal enclosure where a weather-tight joint is required.

Reducing Bushing



Material	Steel
Finish	Galvanized
Thread	NPT
Size	1/2" to 4"
Usage	Use to reduce the entry size of a run of threaded IMC / Rigid conduit.



Lloyd's Register



Phone: +86 022 83377302

Email: info@baolaisteel.com



Stainless Steel Reducing Bushing



Material	Stainless Steel
Finish	SS304 / SS316
Thread	NPSL
Size	1/2" to 4"
Usage	Use to reduce the entry size of a run of threaded IMC / Rigid conduit.

Rigid Male Enlarger



Material	Malleable Iron
Finish	Galvanized
Thread	NPT
Size	1/2" to 1"
Usage	Adapt an outlet hole to next large size.

Rigid Male Enlarger, EG



Material	Steel
Finish	Galvanized
Thread	NPT
Size	1/2" to 1"
Usage	to use with IMC/Rigid Pipe



Pull Corner Elbow Rigid to Rigid



Material	Zinc Die Cast
Finish	Galvanized
Standard	UL 514B
Thread	NPT
Size	1/2" to 1"
Usage	Use to facilitate pulling wires through a 90 degree bend in a run of Rigid or IMC conduit.

Pull Corner Elbow Rigid to Box



Material	Zinc Die Cast
Finish	Galvanized
Standard	UL 514B
Thread	NPT
Size	1/2" to 1"
Usage	Use as a wire pulling elbow to facilitate wire pulling through a sharp bend in a run of Rigid Conduit.

Offset Nipple



Material	Zinc Die Cast
Finish	Galvanized
Standard	UL 514B
Thread	NPT
Size	1/2" to 2"
Usage	Use to provide an offset connection between two outlet boxes or metal enclosures.

Electroform Concrete Slab Pipe Inserts-90 Degree



Material	Malleable Iron
Finish	Zinc Plated
Standard	UL 514B
Thread	NPSM
Size	1/2" to 1"
Usage	For conduit installed in poured concrete slabs. Nail, screw or tack-weld insert to concrete deck form.

Electroform Concrete Slab Pipe Inserts-Straight

EF-50 EF-75 EF-100



Material	Malleable Iron
Finish	Zinc Plated
Standard	UL 514B
Thread	NPSM
Size	1/2" to 1"
Usage	For conduit installed in poured concrete slabs. Nail, screw or tack-weld insert to concrete deck form.



Rigid Conduit Nipple



Material	Steel
Finish	Galvanized
Standard	UL6
Thread	NPT
Size	1/2" to 4"
Usage	Use to extend the length of a run of Rigid or IMC conduit or to connect two steel outlet boxes or metal enclosures together.

Chase Nipple



Material	Zinc
Finish	Galvanized
Thread	NPT
Size	3/4", 1"
Usage	Used with threaded female conduit couplings to connect conduits to electrical boxes and enclosures or are used with locknuts to connect two junction boxes.

Chase Nipple, Insulated



Material	Zinc
Finish	Galvanized
Thread	NPT
Size	3/4", 1"
Usage	Used with threaded female conduit couplings to connect conduits to electrical boxes and enclosures or are used with locknuts to connect two junction boxes.



Steel Chase Nipple



Material	Steel
Finish	Galvanized
Standard	UL6
Thread	NPT
Size	1/2" to 6"
Usage	Used with threaded female conduit couplings to connect conduits to electrical boxes and enclosures or are used with locknuts to connect two junction boxes.

Steel Chase Nipple, Insulated



Material	Steel
Finish	Galvanized
Standard	UL6
Thread	NPT
Size	1/2" to 6"
Usage	Used with threaded female conduit couplings to connect conduits to electrical boxes and enclosures or are used with locknuts to connect two junction boxes.

3-Piece Union



Material	Malleable Iron
Finish	Galvanized
Standard	UL
Thread	NPSL
Size	1/2" to 6"
Usage	Used to connect threaded Rigid or IMC Conduit that are not able to be turned.



3-Piece Union, Steel



Material	Steel
Finish	Galvanized
Standard	UL
Thread	NPSL
Size	1/2" to 6"
Usage	Used to connect threaded Rigid or IMC Conduit that are not able to be turned.

Rigid Union Male



Material	Steel
Finish	Galvanized
Standard	UL
Thread	NPT
Size	1/2" to 4"
Usage	used to connect conduit to a conduit fitting or junction box or a device enclosure.

Rigid Union Female



Material	Steel
Finish	Galvanized
Standard	UL 1242
Thread	NPSL
Size	1/2" to 4"
Usage	used to connect conduit to a conduit fitting or a device enclosure.





Service Entrance Cap Threaded type



Material	Aluminum
Standard	UL 514B
Thread	NPSL
Size	1/2" to 4"

IMC/Rigid One Hole Strap, EG



Material	Galvanized Steel
Size	1/2" to 6"
Usage	Snap-on type Rigid strap with one hole Inverted rib for strength.

IMC/Rigid Two Hole Strap, EG



Material	Galvanized Steel
Size	1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 3-1/2", 4"
Usage	Snap-on type Rigid strap with one hole Inverted rib for strength.





STEEL PIPE SINCE 1991
BAOLAI

Rigid Strut Clamp



Material	Galvanized Steel
Finish	Zinc Plated
Standard	UL E365032
Size	1/2" to 8"
Usage	Use to support IMC/Rigid Conduit from strut channel.

Rigid Conduit Hanger



Material	Steel
Finish	Electro-galvanized
Standard	UL 2239
Packing	Assembled with nut and bolt
Size	1/2" to 4"
Usage	Use to secure and suspend EMT/IMC/Rigid Conduit from overhead supports.



Lloyd's Register



Phone: +86 022 83377302

Email: info@baolaisteel.com