1"~6"





⑦

RG-2M

Combination Roll Groover Patented Design 1"-6"

Design Features

- Can be used manually or with a power drive. Ideal for on-site or flexible grooving tasks
- Featuring a patented design, the RG-2M is a versatile roll grooving tool that supports both manual operation and power drive through a threading machine. Suitable for both batch production and flexible on-site operations.
- Light-duty design for fire-fighting pipelines size range 1"~6" (DN25~DN150),SCH10 to SCH40, optional 8"-12" roll set
- Three-stage gear reduction for smooth, labor-saving operation
- Compact design with a portable toolbox, allowing easy manual operation even in confined spaces

Specifications

Fabrication Capacity:	1"~4"(DN25~DN100,Φ33~Φ114) SCH10/40 Steel Pipe 5"~6"(DN125~DN150,Φ139~Φ168) SCH10/20 Steel Pipe
Max Wall Thickness:	7mm
Operation radius:	210mm / 8 ¼"
Gross Weight:	15kgs
Packing Size:	50*22*53cm

Drive Roller



①


1", 1 ¼"~ 1 ½, 2"~ 6"

Groove Roller



②

1"~6"



③



④



⑤



⑥



Drive Unit

Catalog No.	Description	N.W (kg)	Size(cm)
900001	1"-6" roll grooving assembly	12.5	50*22*53
900002	1"-12" roll grooving assembly	13.7	50*22*53

Standard

Catalog No.	Description	N.W (kg)	Ref No.
911010	Drive roller 1 ¼"~1½" (Φ42~Φ48)	0.7	①
911011	Drive roller 1" (Φ33)	0.7	①
911009	Drive roller 2"~6" (Φ60~Φ168)	0.7	①
912016	Groove roller 1"~6" (Φ33~Φ168)	0.3	②
998036	Ratchet with socket	1.65	③
911016	Support arms(2pcs) for 300 power drive	1.4	④
911015	Drive bar adaptor	1.6	⑤
998034	HDPE tool case	2.7	⑦

Optional

Catalog No.	Description	N.W (kg)	Ref No.
	roll set 8"-12" for Sch10-20 pipe	1.2	①②
998114	Bracket set for horizontal threading machine	1.0	⑥