
Permanent Red FGR

Color Type	Azo
Color Index No.	P.R. 112
CAS NO.	6535-46-2
Structure:	



Description :

Physical Properties :

 Recommend for all kinds of printing inks, Textile printing, also for air-drying paint, baking enamel,high-end automotive coatings and latex lacquer, wood painting

ItemsDataDensity (g/cm³)1.38-1.65Specific Surface Area (m²/g)17-40Oil Absorption (g/100g)35-88

Specific Surface Area (m ² /g)	17-40
Oil Absorption (g/100g)	35-88
PH Value	3.5-7.0
Bulk Destity (lb/gal)	11.5-13.5
Particle size(µm)	0.11

Fastness Properties	Data
Heat Resistance (°C)	200
Light Resistance (Full Shade, 1~8)	6-7
Weather Resistance (1~5)	5
Acid Resistance (1~5)	3
Alkali Resistance (1~5)	4
Alcohol Resistance (1~5)	3
Ester Resistance	4
Ketone Resistance	4
Ketone Resistance	4

Hangzhou Fancheng Chemical Co.,Ltd Add: No. 37 Jinyi Road, Xiaoshan, Hangzhou, China Tel: +86-571-83531793 http://www.finelandpigment.com/

Applications :

	Offset Ink	•
Inks	Gravure Ink	Ø
	UV Ink	•
	Solvent borne	Ø
	Water borne	•
	Automotive paint	•
	Air-drying paint	•
Paints	Baking enamel	•
	Textile printing	•
	Wood painting	•

Remark: •High Recommendation; ©Recommendation; - Limit Suitability

Storage conditions :

Should be sealed for avoiding light and moisture.

Package :

20KG/ Kraft Bag,400kgs per pallet

*Product specific and application information are based upon our current knowledge. They are non-binding and cannot be taken as guarantee. Users must establish the suitability of individual products. We do not accept any liability relating to the use of our products in particular applications.