


Quinacridone Violet

Color Type Quinacridone

Color Index No. P.V.19

CAS NO. 1047-16-1

Structure:



Description :

- High performance violet pigment.
- Recommended for high end coatings, plastic and high grade metal decorative printing ink. Its solvent resistance and heat resistance can reach 300°C in plastic. We have bluish and yellowish for your reference.

Physical Properties :

Items	Data
Density (g/cm ³)	1.5-1.8
Specific Surface Area (m ² /g)	22-85
Oil Absorption (g/100g)	40-70
PH Value	6.5-9
Bulk Density (lb/gal)	12.6-14.8

Fastness Properties	Data
Heat Resistance (°C)	300
Light Resistance (Full Shade, 1~8)	8
Weather Resistance (1~5)	5
Acid Resistance (1~5)	5
Alkali Resistance (1~5)	5

Applications :

Plastic	PP	●
	PVC	●
	PUR	●
	HDPE	●
Paint	Industrial Paint	●
	Metal Decorative	●
Ink	Metal decorative	●

Remark: ●High Recommendation;

◎Recommendation; - Limit Suitability

Storage conditions :

Should be sealed for avoiding light and moisture.

Package :

10KG/Drum

*Product specific and application information are based upon our current knowledge. They are non-binding and cannot be taken as guarantee. Users must establish the suitability of individual products. We do not accept any liability relating to the use of our products in particular applications.

Hangzhou Fancheng Chemical Co.,Ltd

Add: No. 37 Jinyi Road, Xiaoshan, Hangzhou, China

Tel: +86-571-83531793

<http://www.finelandpigment.com/>