


Methyl Violet (PTMA)

Color Type Triphenylmethane Lake

Color Index No. Pigment Violet 3

CAS NO. 1325-82-2

Structure:



Description :

- Lake violet pigment.
- Recommend for ink applications like packaging printing ink, water-based ink and offset printing ink, also can be used for stationery such as carbon paper.

Physical Properties :

Items	Data
Density (g/cm ³)	2.15-2.30
Specific Surface Area (m ² /g)	3.6-4.5
Oil Absorption (g/100g)	41-77
PH Value	4-7
Bulk Destity (lb/gal)	17.9-19.1

Fastness Properties	Data
Heat Resistance (°C)	160
Light Resistance (Full Shade, 1~8)	6
Weather Resistance (1~5)	4
Acid Resistance (1~5)	4
Alkali Resistance (1~5)	4

Applications :

Inks	Offset Ink	●
	Gravure Ink	●
	UV Ink	◎
	Solvent borne	●
	Water borne	●

Remark: ●High Recommendation;

◎Recommendation; - Limit Suitability

Storage conditions :

Should be sealed for avoiding light and moisture.

Package :

25KG/Kraft Bag

*Product specific and application information are based upon our current knowledge. They are non-binding and cannot be taken as guarantee. Users must establish the suitability of individual products. We do not accept any liability relating to the use of our products in particular applications.

Hangzhou Fancheng Chemical Co.,Ltd

Add: No. 37 Jinyi Road, Xiaoshan, Hangzhou, China

Tel: +86-571-83531793

<http://www.finelandpigment.com/>