


Perylene Red BL

Color Type Perylene
Color Index No. P.R.149
CAS NO. 4948-15-6
Structure:



Description :

- Pure slight bluish red, high color strength, high heat resistance and good light fastness. Excellent migration resistance in soft PVC.
- Mainly recommend for plastic, 300-320 °C in PC,PA,PET, ABS, PP etc applications with excellent heat stability and chemical resistant properties.

Physical Properties :

Items	Data
Density (g/cm ³)	1.40
Specific Surface Area (m ² /g)	56
Oil Absorption (g/100g)	66
PH Value	5-8
The average particle size (nm)	35

Fastness Properties	Data
Heat Resistance (°C)	300-320
Light Resistance (Full Shade, 1~8)	8
Weather Resistance (1~5)	5
Acid Resistance (1~5)	5
Alkali Resistance (1~5)	5

Applications :

Plastic	PVC	●
	PE	●
	PP	●
	ABS	●
	PC	●
	PA	●
	POM	●

Remark: ●High Recommendation;

◎Recommendation

- Limit Suitability

Storage conditions :

Should be sealed for avoiding light and moisture.

Package :

10KG-25KG/ Kraft Bag

*Product specific and application information are based upon our current knowledge. They are non-binding and cannot be taken as guarantee. Users must establish the suitability of individual products. We do not accept any liability relating to the use of our products in particular applications.

Fineland Chem Co., Ltd

Add: Xianggong Village, Hezhuang Town, Xiaoshan District, Hangzhou, China

Tel: +86-571-83531793

<http://www.finelandpigment.com/>