


Superfast® Yellow GYP

Color Type Quinphthalones

Color Index No. P.Y. 138

CAS NO. 30125-47-4

Structure:



Description :

- High performance yellow pigment.
- Recommend for plastic applications with excellent weathering resistant, heat stability and chemical resistant properties.

Physical Properties :

Items	Data
Density (g/cm ³)	1.82
Specific Surface Area (m ² /g)	24
Average grain size	390
Resistance to warping(HDPE)	low

Fastness Properties	Data
Heat Resistance (°C)	280
Migration Resistance ((1~5))	4-5
Weather Resistance (1~5)	4-5
Acid Resistance (1~5)	5
Alkali Resistance (1~5)	5

Applications :

Plastic	HDPE	●	PS/SAN	●
	LDPE	●	ABS	◎
	PP	●	PC	◎
	PVC-U	●	PBT	◎
	PVC-P	●	PA	-
Paints	Automotive OEM	●	PA	-
	Car Refinish	●	PAN	◎

Remark:

- HighRecommendation;
- ◎Recommendation;
- Limit Suitability

Storage conditions :

Products should be stored in a ventilated, dry, cool warehouse, must be acidic, alkaline and other chemicals and flame isolation

Package :

20KG/ Kraft Bag

20KG/ Drum

Hangzhou Fancheng Chemical Co.,Ltd

Add: No.37, Jinyi Road, Xiaoshan, Hangzhou, Zhejiang, China

Tel: 0086-571-83531793

Email: sales@finelandpigment.com