



Product Service

Attestation of Conformity

No. E8A 104143 0001 Rev. 00

Holder of Certificate: **Dongguan Dadi Electronic Technology Co.,Ltd.**
3/F, No.10 Sanjiang Industrial Area, Hengli Town
523460 Dongguan City, Guangdong Province
PEOPLE'S REPUBLIC OF CHINA

Name of Object: **Safety Light Curtain**

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with all essential requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 64713190116901

Date, 2019-04-18 (Tony Liu)

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證書 ◆ CERTIFIKAT ◆ CERTIFICADO ◆ CERTIFICAT

A4 / 07.17



Product Service

Attestation of Conformity

No. E8A 104143 0001 Rev. 00

Model(s):

QA TT/UU-VVVVWXY, QR TT/UU-VVVVWXY,
QRF TT/UU-VVVVWXY, QC TT/UU-VVVVWXY,
QZ TT/UU-VVVVWXY, QE TT/UU-VVVVWXY,
QT TT/UU-VVVVWXY

TT = 04, 06, 08, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34,
36, 38, 40, 42, 44, 46, 48, 50, 52, 54, 56, 58, 60, 62, 64, 66, 68,
70, 72; This is the beam (increasing in even numbers), beams.
UU = 10, 14, 20, 25, 30, 40, 80 ; which represents the distance
between beams, only the following: 10 , 14 , 20 , 25 , 30 , 40 ,
80 .

VVVV = 0050, 0070, 0090, 0110, 0130, 0150, 0170, 0190, 0210,
0230, 0250, 0270, 0290, 0310, 0330, 0350, 0370, 0390, 0410,
0430, 0450, 0470, 0490, 0510, 0530, 0550, 0570, 0590,
0610, 0630, 0650, 0670, 0690, 0098, 0126, 0154, 0182,
0210, 0238, 0266, 0294, 0322, 0350, 0378, 0406, 0434
, 0060, 0100, 0140, 0180, 0220, 0260, 0300, 0340, 0380, 0420,
0460, 0500, 0540, 0580, 0620, 0660, 0700, 0740, 0780,
0820, 0860, 0900, 0940, 0980, 1020, 1060, 1100, 1140,
1180, 1220, 1260, 1300, 1340, 1380, 1420, 0125, 0175, 0225,
0275, 0325, 0375, 0425, 0475, 0525, 0575, 0625, 0675, 0725
, 0775, 0150, 0210, 0270, 0330, 0390, 0450, 0510, 0570,
0630, 0690, 0750, 0810, 0870, 0930, 0120, 0200, 0280,
0360, 0440, 0520, 0600, 0680, 0760, 0840, 0920, 1000,
1080, 1160, 1240, 1320, 1400, 1480, 1560, 1640, 1720,
1800, 1880, 1960, 2040, 2120, 2200, 2280, 2360, 2440, 2520,
2600, 2680, 2760, 2840, 0240, 0400, 0560, 0720, 0880, 1040,
1200, 1360, 1520, 1680, 1840, 2000, 2160, 2320, 2480

means that the distance(mm) from the first beam to the last one is the protection height.

W=Blank or 1, 2; 1: One set of output modes; 2: Two sets of output modes

X=A, B, C, D: represents the output mode, there are four output modes A indicates: NPN NC; B indicates: PNP NC; C indicates NPN NO; D: indicates: PNP NO; Y = A, B, C, D, E, F, G, H, I; Represents induction distance: A: 0.3-3M; B: 0.3-6M; C: 0.3-10M; D : 0.3-15M; E: 0.3-20M; F: 0.3-25M; G:0.3-30M; H:0.3-40M, I:0.3-60M

Trade name:

DADISICK

Description of Object:

Rated voltage: DC 12-24V
Max current: 200mA

Tested according to:

EN 61000-6-2:2005
EN 61000-6-4:2007/A1:2011

Page 2 of 2

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

