



- Built for heavy-duty grooving jobs, model RG-8X is ideal for high-volume grooving of various size steel pipes in workshop and construction sites
- Equipped with a high-power motor and high-strength gearbox, the machine is built for long-term, continuous operation
- One-Push™ groove roller system: instant pipe engagement with a single press, quick and effortless operation
- Heavy-duty groove rollers and drive rollers (standard 1"-12", can choose 14" for option) with interlocking structure ensures precise control of the pipe sealing surface length
- Titanseal™ fully enclosed hydraulic pump with innovations: ultra-fast feed, dual oil-reservoir structure, and multi-seal protection — doubling efficiency and ensuring ultra-long service life without oil changes
- Working speed up to 32 RPM, boosting efficiency by 39%

Specifications

Fabrication Capacity: 1"~12"(DN25~DN300, Ф33~Ф325)

SCH10/40 Steel Pipe

Max Pipe Wall Thickness: Output Speed: 32 R.P.M

220V/ 1500W 1Ph Motor:

Net Weight: 142kgs

Innovative **Gruv-X series**

						B 4			
M	2	0	h	ın	е	N	\cap		C
_	a	•			_	1.	ıv	u	LO

Catalog No.	Power	Voltage	Frequency		
Gruv-X	1500W/1Ph	220V	50/60Hz		
Gruv-X	1500W/1Ph	110 V	50/60Hz		

*Support Voltage customization

