

# Mid-range Series Checkweigher

Unqualified automatic elimination

## Product Features

- ① Powerful calculation function, recording various test data;
- ② Three-level operation authority management, supporting self-set passwords;
- ③ Touch screen operation, user-friendly design;
- ④ Adopting variable frequency control motor, the speed can be adjusted according to needs;
- ⑤ The conveyor belt is easy to disassemble and install, easy to install and maintain, and easy to clean.



## Product technical parameters

|                          |  |                   |   |
|--------------------------|--|-------------------|---|
| Product model            | SC2-8040L15  | Storage formula   | 100 types                                   |
| Display division         | 0.001kg  | Belt speed        | 5-90m/min                                   |
| Inspection weight range  | 0.05-15kg  | Power supply      | AC220V±10%                                  |
| Weight checking accuracy | ±3-10g   | Shell Material    | Stainless steel 304                         |
| Size of weighing section | L 800mm*W 400mm  | Data Transmission | USB data export                             |
| Suitable product size    | L≤600mm; W≤400mm   | Sorting Section   | Standard 1 section<br>(optional 3 sections) |
| Elimination method       | Push rod type, swing wheel type, and top lifting transplanting are optional                                  |                   |   |
| Optional Features        | Real time printing, code reading and sorting, online code spraying, online code reading, and online labeling |                   |   |

Note \* The maximum speed and precision of weight checking vary according to the actual products and installation environment.  
Type selection should pay attention to the movement direction of the product on the belt line. For transparent or translucent products, please contact us.