

# Assembly Line Checkweigher

## Product Features

- ① Touch start/stop button;
- ② The upper and lower weight limit parameters can be set arbitrarily;
- ③ Optional stop weight check or continuous weighing, push rod rejection and sound and light alarm when the product is abnormal;
- ④ Chinese and English touch interface, multiple recipe storage, password authority management, weighing record, intelligent fault detection, etc.;
- ⑤ Non-standard customization can be carried out according to customer requirements;
- ⑥ Directly set up in the middle of the assembly line, saving manpower and space.



## Product technical parameters

Product model	SC-PR-4530L3	Storage formula	100 types
Display division	0.1g	Belt speed	5-40m/min
Inspection weight range	1-3000g	Power supply	AC220V±10%
Weight checking accuracy	±0.5-2g	Shell material	Carbon steel spray painting
Size of weighing section	L 450mm*W 300mm	Data transmission	USB data export
Suitable product size	L≤750mm; W≤600mm	Sorting section	Standard 2 section, optional 3 sections
Elimination method	Push rod type and paddle type optional		
Optional Features	Real time printing, code reading and sorting, online code spraying, online code reading, and online labeling		

Note \* The maximum speed and precision of weight checking vary according to the actual products and installation environment.  
Type selection should pay attention to the movement direction of the product on the belt line. For transparent or translucent products, please contact us.