

Parameter	Unit	Value
Basic Parameter		
Motor type		Brushless servo motor
Voltage range	V	12~24
Peak torque	N.M	1
Rated torque	N.M	0.4
Peak current	A	6
Continuous current	A	1.5
Instantaneous power	W	144
Rated power	W	36
Outer diameter	mm	60
Minimum inner diameter	mm	16
Height	mm	33
Weight	g	290
Motor Parameter		
Number of pole pairs	Pair	14
Wire resistance	Ohm	1.35
Wire inductance	uH	800
Torque constant	N.M/A	0.21
Speed constant	v/krpm	21.8
Control Accuracy Parameter		
Maximum speed	rpm	2700
Minimum speed	rpm	0.01
Encoder type		Single turn absolute value
Encoder resolution	bit	16
[Position] Repeated positioning accuracy	deg	+/-0.006
[Position] Absolute accuracy	deg	+/-0.006
[Speed] Rate of speed change	%	<+/-0.5
[Speed] Speed resolution	Hz	0.0001
Dynamic Parameter		
Rotor inertia	kg*mm^2	59.7
Bearing type		71804AC
Bearing accuracy		P5
Bearing dynamic load Cr	kN	3.6
Bearing static load C0r	kN	2.5
Working temperature range	deg C	5~50
Noise	dB	<50
Interface Parameter		
Number of interfaces		7
Control interface 1		CAN&CAN FD
Control interface 2		PWM
Configuration interface		RS485
The secondary encoder interface		Only support our hollow encoder module
Supported modes (may vary with firmware version)		
Position mode		Position speed current three closed loop mode
Speed mode		Speed closed loop mode
Current(torque) mode		Torque closed loop mode